

J. Dominis. Sheeti, 2 Sheets.
Ship's Implement.



J. Jominis. Sheets, 2 Sheets.

Ship's Implement.

Nes,790. Patented Sept. 30, 1842.



UNITED STATES PATENT OFFICE.

JNO. DOMINIS, OF THE SANDWICH ISLANDS.

INSTRUMENT FOR MEASURING SAILS.

Specification of Letters Patent No. 2,790, dated September 30, 1842.

To all whom it may concern:

Be it known that I, John Dominis, a citizen of the United States of America, but now residing in the Sandwich Islands, in the Pacific Ocean, have invented new and useful mathematical scales and tables for determining the gores, roaches, and proportions of sails for cutting the same from rolls of canvas.

The said invention, the principles thereof, and manner in which I have contemplated the application of the same by which
it may be distinguished from others of a
like character, together with such parts or
combinations I claim as new and desire Letters Patent therefor granting to me an exclusive property in the same for fourteen
years, I-have herein set forth and described,
which description taken in connection with
the accompanying drawings herein referred
to forms my specification.

As sails of different kinds and for different vessels are formed of strips of cloth or canvas sewed together, after they are cut to proper shapes and lengths, and as it is customary to cut said strips from what is usually termed a roll or bolt of canvas, it becomes desirable to accomplish the same, with as little waste of material as possible, or in other words so to measure the lengths and gore of each strip that when the whole are sewed together, the sail thus formed shall possess the required shape, and in nautical language set well when adjusted and exposed to the action of the wind.

In order that the use and adaptation of my improvements may be more particularly understood, I shall proceed to illustrate the mode usually practiced of cutting the cloths of a sail from a long or extended strip of canvas.

We will suppose for the sake of explanation that we wish to cut up a roll of canvas for the purpose of converting the same into a sail usually termed a jib. To cut the first cloth (presuming the canvas is square on the end) it is necessary to set up from the end a certain determined distance (called the gore on the foot, and which we will suppose six and one half inches), on either

selvage of the canvas and there make a suitable mark. Then cut from the said mark diagonally across the canvas to the extreme point of the opposite selvage and thus we shall have formed the foot gore for the first 55 cloth. Next measure up on the selvage from the foot or mark above mentioned the length of the after leach (which suppose forty two feet), then from the extremity of the distance so measured set downward an- 60 other certain determined distance called the gore on the stay and which we will suppose to equal four feet and four inches. Next following the filling thread so marked across the strip of canvas to the opposite 65 selvage and make a suitable mark thereon, which mark will be in a line perpendicular to the selvage. Next cut the cloth from the last mentioned mark diagonally to the mark, denoting the length of the first 70 cloth and thus we form the stay gore for the first and second cloths. Turn the canvas so as to bring the longer selvage even in a line with the shorter selvage of the first cloth. Measure down by this cloth for the 75 length of the second cloth and mark it; thence take a thread as before to the opposite selvage; thence set off six and one-half inches (the foot gores) downward; mark it and cut diagonally as before to the mark 80 denoting the length of the second cloth on the opposite selvage, and thus we obtain the foot gore or slope of the second and third cloths. Turn the canvas on the foot, as before, on the head, and continue measuring 85 turning and cutting until all the cloths are so prepared.

The above is the process by which a bolt of sail cloth is generally cut up, and from the same it will be easily seen that in order 90 to prevent waste and to make the cloth come together so as to give to the sail its intended form when finished, great care is requisite in finding the true distances to measure down on the selvage to obtain the gores on 95 the stay and foot.

Having thus premised, I shall now proceed to explain the construction and application of the mathematical scales and tables

Figure 1, represents the different scales attached to their board. Two scales A and B being placed parallel to each other and at a suitable distance apart are screwed 5 down or otherwise properly secured to a table or board a b c d, Fig. 1. The inner edge of the scale A is divided into inches, which divisions are subdivided into tenths, or in any other convenient manner. A 10 semi circle e f g, graduated to degrees is described on the scale A as seen in the drawing the chord of the semi circle being formed by the inner edge of the rulers. The opposite scale B has its inner edge di-15 vided and subdivided in a similar manner to the first; and each of these scales has an elongated slot h i j k formed in it parallel with its inner edge. Each of the slots is placed directly over a suitable groove or 20 channel cut out of the wood under the same, and which is of sufficient breadth and depth to receive and allow full play back and forth the heads of common screws l m n o, in which screws the milled clamping nuts p, q, 25 r, s, are screwed, the said nuts serving to confine the rulers E, F, &c. in different positions in which they may be adjusted to each other on the board as will be hereafter explained. The heads of the screws l, m, 30 n, o being larger in diameter than the width of the slots h, i, j, k, are drawn upwards against the underside of the scales A, B, or sides of the slots, when the milled clamping nuts are screwed down, and thus the rulers 35 or scales E, F, are confined when adjusted to any particular position. A section of one of the screws, milled nuts, scales, and channel or groove under the latter is given in Fig. 7 where b is the screw, a the milled nut, 40 d d the scale, e the channel in the woodwork, for the head c of the screw b to move in.

The center of the semicircle e f g has a screw 8 projecting perpendicularly there-45 from, on which a clamping nut or head U is secured and serves to confine the rulers C and D, &c., in any desirable positions. The graduations or divisions of the ruler A commence at the center of the semicircle 50 e f g, and are numbered or extend each way as represented by the Figs. 3, 4, &c., in the figure. The divisions of the ruler B are similar and are directly opposite those of the ruler A as exhibited in the drawing— 55 that is to say, the straight or base line, from the center of the screw t or semicircle e f g, to the zero of the opposite ruler, is perpendicular to the inner edges of each ruler.

The rulers C, D are formed as represent-60 ed in the drawing, in which it will be observed that their ends resting on or near the graduated semicircle e f g, are pointed and their edges chamfered for the conven-

ience of reading the angular distances of each ruler on the semicircle, which will be 65 hereafter more particularly explained. The rulers C and D are divided into inches and subdivided into tenths commencing from the center of the semicircle e f g, and denoted by Figs. 2, 3, 4, 5, &c., as represented in the 70 drawing.

Two other scales or rulers E F are joined together, at one end of each, by a common rule joint, so as to be easily opened and closed or adjusted to any required angle 75 with each other. Each ruler has an elongated slot v w—v w cut through the same, through which the clamp screws pass, which confine the rulers in any required position on the board. At the point of junction of 80 the rulers E F, and situated under the same, a full graduated circle x is so affixed as to be freely revolved or turned about on its axis, the said axis passing through the center of the joint of the rulers, and having a 85 small wire point or pin y projecting upward perpendicularly therefrom, see Figs. 9 and 10. Small holes z z z are drilled through the divisions of the rulers C and D and the pin y is passed through either of these 90 heles according to circumstances which will be more particularly understood or explained hereafter.

The circle x is graduated to degrees and has a ruler G connected to it, as seen in the 95 figure, and whose ends project beyond the circle as therein denoted. The diameter of the circle being extended beyond the circumference is marked on the projecting ends by a line passing through the center 100 of the upper face of the entire ruler, as will be seen by reference to the drawing.

Another ruler H formed and divided into inches and lengths and having clamp screws and nuts as represented in the drawing, will 105 be hereafter explained as also a curved ruler I one end of which is placed on the center pin or screw t and is formed with holes and otherwise shaped as represented partly by dotted lines and partly as otherwise exhib- 110 ited in the drawing. The other end of the ruler I has an elongated slot b' c', through which a sliding screw passes upward from the slot in the ruler B, and by the milled nuts thereon we are enabled to confine the 115 ruler in whatever position we place the same on the board a b c d as will be readily understood by inspection of the drawing. The ruler I is for obtaining the roach and sweep of sails as will be hereinafter ex- 120 plained.

A card or sheet of paper e' f' g' h' is laid on the board a b c d between the rulers Aand B. One edge of the paper viz, e' g'is to be cut perfectly straight and is to be 125 placed in continuity with the inner or grad-

uated edge of the ruler A, and to this edge lines are drawn parallel to the same and to each other at a distance therefrom and apart from each other, proportionate to the widths of cloth or canvas used in making the sail. For canvas of different widths there should be separate sheets of paper, proper ruled for each, which may be used as occasion requires.

and the seams take up one inch thereof we rule the lines at a distance apart from each other proportionate to twenty eight inches, which if we use a scale of five feet to an inch, would equal seven fifteenths of an inch. Also for cloths of twenty three inches width, deducting one inch for the seams, we

have twenty two inches, which if we use the above scale of five feet to an inch, will give us eleven thirteenths of an inch, for the distance for ruling the lines apart from each other; and so on with any other width of canvas. The spaces between the ruled lines represent the strips of canvas in each sail as will be hereafter explained, and are numbered 1, 2, 3, 4, 5, &c., as seen in the drawing.

Having thus described the construction of the mathematical scales, I shall now proceed to explain the method of forming the 30 tables accompanying the same, which are herein given and make a part of my specification.

Cloths of 22 inches.

	··-		٠.		······································	·														······································	<u>.</u>	· · ·
.1	No. 1	No.	2	No. i	No	. 4	No. 5	No. 6	No. 7	No. 8	No. 9	No. 10	No. 11	No. 12	No. 13	No. 14	No. 15	No. 16	No. 17	No. 18	No. 19	No. 20
CHICACACACACACACACACACACACACACACACACACAC	36 16 37 17 38 17 39 18 40 19 41 19 42 20	$\frac{1}{2} \frac{2}{3} \frac{4}{4} \frac{5}{6} \frac{6}{7} \frac{8}{8} \frac{9}{10} \frac{1}{12} \frac{1}{12$	11 12 13 14 15 16 17 18 19 19 21 22 22 25 26 28 29 31 32 33 36 37 38 41 41 41 41 41 41 41 41 41 41 41 41 41	14 15 16 17 18 19 20 21 22 22 22 22 23 24 25 25 26 27 28 29 31 32 34 44 44 45 45 45 45 45 45 45 45 45 45 45	123456789023456890134578902457801356802457024 12356789023456890134578902457801356802457024	22 24 25 25 26 36 37 39 41 43 45 47 49 49 51 55 55 57 57 57 57 57 57 57 57 57 57 57	14 36 36 36 36 36 36 36 36 36 37 36 38 30 42 42 43 43 44 43 44 43 44 43 44 43 44 43 44 43 44 43 44 43 44 43 44 43 45 44 46 42 47 43 48 44 49 44 40 44 43 44 44 44 45 44 46 44 47 44 48 44 49 44 44 44 44 44 45 44 46 44 47 44 48 44 49 44 44 44 44 44 44 44 44 44 44	1 2 3 4 5 6 7 8 9 10 12 13 13 13 13 14 15 16 17 18 19 10 11 12 13 13 15 16 17 18 19 10 11 11 11 11 11 11 11 11 11 11 11 11	1 2 3 4 14 16 19 11 12 3 14 15 16 17 18 18 18 18 18 18 18 18 18 18 18 18 18	1 3 6 9 12 15 18 29 15 18 29 18 18 18 18 18 18 18 18 18 18 18 18 18	19 10 10 10 10 10 10 10 10 10 10 10 10 10	1 2 3 4 5 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	14 60 15 65 16 74 18 18 19 16 18 19 20 108 21 108 22 103 23 108 24 108 25 113 26 119 27 123 29 134 31 145 32 151 33 157 34 163 37 183 39 196 40 203 41 218 43 236 44 234 43 236 44 234	8 37 9 47 11 12 56 13 14 56 13 16 76 14 17 86 15 16 17 16 17 86 17 18 91 20 102 21 102 22 107 23 112 24 123 26 129 27 134 28 146 30 152 31 159 32 165 33 172 34 178 35 185 36 192 47 146 48 185 49 146 40 152 41 188 42 188 43 185 44 185 45 185 46 185 47 185 48 1	14 77 15 77 16 88 17 18 18 98 19 104 21 116 23 122 24 128 25 134 26 146 27 159 31 179 32 179 33 186 34 193 35 208 37 215 38 215 38 215 40 240 41 249 42 25 43 26 44 27 45 27 46 28 47 28 48 29 49 29 40 24 40 24 41 24 42 25 43 26 44 27 45 26 46 27 47 27 48 27 48 48 27 48 48 27 48 48 27 48 48 48 48 48 48 48 48 48 48 48 48 48	1 11 16 17 18 18 18 18 18 18 18 18 18 18 18 18 18	14 82 15 88 16 101 17 101 18 107 19 120 21 133 23 140 24 147 25 161 27 168 29 183 30 198 31 206 33 214 34 223 36 240 37 249 42 298 43 309 44 320 44 320 44 320	14 87 15 100 17 106 18 120 18 120 20 128 21 134 22 140 23 148 24 157 25 170 27 178 28 193 30 202 31 203 32 218 33 226 34 235 35 244 36 253 37 262 38 272 39 282 40 293 41 326 42 314 43 326 44 336 44 336 44 336 44 336 44 336 44 336 44 336 45 34 46 34 36	14 93 15 100 16 107 17 114 18 129 20 136 21 144 22 150 23 167 25 167 26 182 27 191 28 199 29 207 30 216 31 225 32 234 33 243 34 252 36 172 37 282 39 303 40 314 41 325 42 337 43 349 44 361	$\begin{array}{c} 1 & 27 \\ 24 & 24 \\ $	17 128 18 136 19 144 20 152 21 160 22 169 23 177 24 186 25 195 26 204 27 213 28 222 29 232 30 242 31 252 32 262 33 272 34 282 35 293 36 304 37 315 38 326 39 338 40 351 21 363	14 110 15 126 17 134 18 143 19 152 20 169 21 178 23 188 24 196 25 215 27 224 28 233 29 244 30 254 31 264 32 275 33 286 34 297 35 368 36 320 37 320 37 320 38 344 39 357 40 370 41 382 42 396 43 425

Cloths of 22 inches.

\mathbf{For}_{\cdot}	l cloth.	For	1 cloth.	For 1	l cloth.	For 1 cloth.			
Deg. 46 47 48 49 50 51 52 53 54 55	$Ft.\ in. \ 1\ 11\ 2\ 0\ 2\ 1\ 2\ 3\ 2\ 3\ 4\ 2\ 5\ 6\ 2\ 7$	Deg. 56 57 58 59 60 61 62 66 64 65	$Ft.\ in.\ 2\ 9\ 2\ 10\ 2\ 11\ 3\ 4\ 3\ 5\ 3\ 7\ 3\ 9\ 3\ 11$	Dcg. 66 67 68 69 70 71 72 73 74 75	$Ft.\ in.\ 4\ 1\ 4\ 4\ 6\ 4\ 9\ 5\ 8\ 6\ 0\ 6\ 5\ 6\ 10$	Deg. 76 77 78 79 80 81 82 83 84 85	$Ft.\ In.\ 7\ 4\ 7\ 11\ 8\ 8\ 9\ 5\ 10\ 4\ 11\ 7\ 13\ 00\ 14\ 11\ 17\ 5\ 20\ 11$		

Cloths of 28 inches.

				· .															
No.1	No. 2	No. 3	No. 4	No. 5	No. 6	No. 7	No. 8	No. 9	No. 10	No. 11	No. 12	No. 13	No. 14	No. 15	No. 16	No. 17	No. 18	No. 19	No. 20
18 9 19 10 20 10 21 11 22 12 23 12 24 12 25 13 26 14 27 14 28 15 30 16 31 17 32 17 33 18 34 19	1 2 3 4 5 6 7 8 9 10 11 2 13 14 15 16 17 18 19 20 21 22 24 25 27 28 30 31 32 33 34 35 42 44 45 4	1 2 3 4 5 6 7 9 10 12 13 14 15 16 18 19 11 12 13 14 15 16 18 19 11 12 13 14 15 16 17 18 19 12 13 14 15 16 17 18 19 12 13 14 15 16 17 18 19 12 13 14 15 16 17 18 19 12 13 14 15 16 17 18 19 11 12 13 14 15 16 17 18 19 18 18 18 18 18 18 18 18 18 18 18 18 18	1 2 4 6 8 10 12 14 16 8 10 12 12 12 12 12 12 12 12 12 12 12 12 12	1 2 3 4 5 6 7 8 9 10 12 13 14 15 15 17 12 13 14 15 15 17 12 13 14 15 15 17 12 13 14 15 15 15 15 15 15 15 15 15 15 15 15 15	1 2 3 4 5 6 7 8 9 10 13 13 14 15 15 15 15 15 15 15 15 15 15 15 15 15	1 2 3 4 5 6 7 8 9 10 12 12 13 14 15 16 17 8 9 10 12 13 14 15 16 17 18 19 10 11 12 13 14 15 16 17 18 19 10 11 12 12 13 13 13 13 13 13 13 13 13 13 13 13 13	1 2 3 4 5 6 7 8 9 10 12 13 14 15 15 6 6 4 15 15 16 15 16 15 16 16 16 16 16 16 16 16 16 16 16 16 16	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	1 2 3 4 5 6 7 8 9 10 12 3 4 4 5 5 6 7 8 9 10 12 3 14 5 6 6 5 7 5 10 12 3 14 5 6 6 5 7 5 10 12 3 14 12 12 12 12 12 12 12 12 12 12 12 12 12	13 77 14 77 15 88 16 18 94 18 100 19 112 21 124 23 131 24 137 25 143 26 171 30 185 31 193 32 208 34 216 37 232 38 241 39 249 40 258 41 268 42 27 43 28 44 298	1 2 3 4 5 6 7 8 9 10 1 2 3 5 4 4 7 8 9 10 1 2 3 1 3 1 3 1 3 1 4 1 5 3 1 1 2 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1	1 2 3 4 5 6 7 8 9 10 1 25 38 44 5 8 6 7 7 8 9 10 1 12 3 14 15 12 6 14 17 13 14 15 12 14 15 12 14 15 12 14 15 12 14 15 12 14 15 12 14 15 12 14 15 12 12 12 12 12 12 12 12 12 12 12 12 12	1 2 3 4 5 6 7 8 9 10 12 3 4 4 4 5 5 5 6 6 7 8 9 10 12 3 13 14 3 15 16 6 12 12 13 14 3 15 16 17 19 12 12 13 14 15 16 17 19 12 12 12 13 14 15 16 17 19 10 12 12 12 13 14 15 16 17 19 10 10 10 10 10 10 10 10 10 10 10 10 10	1 2 3 4 5 6 7 8 9 10 1 2 1 2 1 3 1 4 5 5 6 7 8 9 10 1 1 2 1 3 1 4 5 1 5 3 1 1 2 1 1 3 1 4 5 1 5 3 1 1 2 1 1 3 1 4 5 1 5 3 1 1 2 1 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1	3 4 39 4 39 5 4 7 8 9 10 12 13 14 15 15 15 16 17 18 16 17 18 16 17 18 16 17 18 16 17 18 18 17 18 18 18 18 18 18 18 18 18 18 18 18 18	1 2 3 4 2 5 3 3 4 2 5 5 8 7 6 7 8 9 3 10 2 13 14 15 1 15 1 15 1 15 1 15 1 15 1 15	1 2 3 4 5 6 7 8 9 8 1 1 2 3 6 4 4 4 5 6 7 8 9 8 1 1 2 6 1 1 1 2 6 1 1 1 1	1 2 3 4 5 6 7 8 9 19 28 37 47 6 6 5 7 8 9 10 11 21 21 21 21 21 21 21 21 21 21 21 21	1 20 3 4 39 4 5 6 7 8 9 10 1 10 1 10 1 10 1 10 1 10 1 10 1 10

Cloths of 28 inches.

For I	i cloti	h.	For	1 clot	h.	For	1 clot	h.	For 1 cloth.			
Deg. 46 47 48 49 50 51 52 53 54 55	Ft. 2 2 2 2 3 3 3 3 3 3	$in. \\ 5 \\ 6 \\ 7 \\ 8 \\ 9 \\ 11 \\ 0 \\ 1 \\ 2 \\ 4$	$Deg. \\ 56 \\ 57 \\ 58 \\ 59 \\ 60 \\ 61 \\ 62 \\ 63 \\ 64 \\ 65$	F1. 3 3 4 4 4 4 5	in. 5 7 9 11 1 2 4 7 9 0	$Deg. \\ 66 \\ 67 \\ 68 \\ 69 \\ 70 \\ 71 \\ 72 \\ 73 \\ 74 \\ 75 \\ .$	Ft. 5 5 6 6 7 7 8 8	in. 3691592728	Deg. 76 77 78 79 80 81 82 83 84 85	Ft. 9 10 11 12 13 14 16 19 22 26	in 0 1 0 3 7 0 2 7	

These tables are produced by trigonometrical calculations on the principle of having the course and departure given to find the difference of latitude. The course may be 5 supposed to represent the angle, which the two sides of a sail make with each other, denoted in the tables by the sign —°— for degrees, the departure the width of canvas to be connected into a sail—represented in 10 the tables by the heading "cloths of 22 inches," "cloths of 28 inches," &c. and the difference of latitude the depth to be measured up or down on the selvage for obtaining the gore on the foot, stay or leach as 15 hereinbefore explained, and which is exhibited in each of the columns adjacent to

those denoting degrees. This latter is arranged in the tables to the nearest inch, fractions of inches being omitted as of no importance in practice.

Columns No. 1, No. 2, &c., to No. 20 rep-20 resent the degrees and departure or depth of gore for any numbers of breadths of cloths of canvas in the sail, corresponding to the number of the column. For instance in the table of "cloths of 22 inches," if we wish to 25 ascertain the whole gore in fifteen cloths the angle of gore being twenty-five degrees we look at 25° in the column of degrees of No. 15 and opposite to it in the right hand adjacent column we have 154 as the whole 30

depth of gore. The process of finding the depth is as follows:

$$\frac{\log. \text{ cosine } 25^{\circ}}{\log. 330}$$
 = No. of inches in 15 cloths = $\frac{\log. \text{ sine } 25^{\circ}}{\log. 154}$ approximately

or as expressed in figures

$$\frac{\log. \cos ine \ 25^{\circ} = 9.95728}{\log. \ 330 = 2.51851} = \frac{\log. \sine \ 25^{\circ} = 9.62595}{\log. \ 153.87 = 2.18718}$$

Therefore for 153.87 we insert 154 in the tables.

Having thus found the whole depth of gores one-fifteenth of 154 or $10\frac{1}{4}$ inches (near 5 enough for practice) will give the depth for one cloth which is nearer by one-quarter of an inch than is denoted in the double column No. 1, of the table against 25 degrees. I have here given but two tables as these are 10 amply sufficient to exhibit the method on which others for cloths of less or greater

width may be constructed. Having thus explained the principles on which the tables are calculated, their appli-15 cation in practice will be easily understood by the following explanation of finding the gores of different sails. Suppose we desire the stay and foot gores of a jib we proceed as follows. Fig. 2, represents a jib the di-20 mensions of which we will suppose to be equal to forty-five feet on the stay B C; twenty-six feet on the foot or A B and thirty-three feet on the after leach or A C. If desired to find the stay and foot gores, 25 represented by C a for the former and c d for the latter we arrange the scales as seen in Fig. 3; that is to say we take a distance h f on D of five inches and two-tenths of an inch which, as the scale is five feet to an 30 inch, is the required distance, representing twenty-six feet. Next take on ruler A a distance g h equal to six inches and sixtenths of an inch, this being the proportional distance for thirty-three feet, the 35 length of the after leach. Lastly take nine inches from f to g on ruler E, first placing the upright point y Fig. 1, of the center of the rulers E F, through the small hole in the division of ruler D expressing five 40 inches of two-tenths of an inch. Then bring the division expressing nine inches on the edge of ruler E to correspond with the division six inches and six-tenths of an inch on ruler A, and turning down the 45 clamping nuts the space f g h, Fig. 3 will | 3, or so that the curve of its upper edge shall parallel lines on the card or paper under the ruler showing the number of cloths or strips of canvass in the same. The index i of the

50 ruler D will denote in the graduated semi-

circle e f g Fig. 1, or e' f' g' Fig. 3 the

numbers of degrees in the angle of the foot

gore, which we will suppose to be eight de-

grees (8°) that is the angle c e d Fig. 2, is equal to eight degrees. In the table headed 55 "cloths of 28 inches" we find against 8° in the double column No. 1, four inches (4) inches) as the depth of the foot gore for each cloth or c d Fig. 2=4 inches. But if we wish to obtain this measurement more 60 exactly, we have only to count the number of cloths in the sail, which in Fig. 3 is found to be eleven. Then looking in double column No. 11, against 8° we have 43 inches for the whole gore; which divided by 11, 65 (the number of cloths) gives a result of $3\frac{10}{11}$ inches, as the true depth of the foot gore of each cloth. In practice four inches

are sufficiently near.

The next operation is to ascertain the an- 70 gle of the stay gore or C b a, Fig. 2. The graduated circle x Fig. 1, with the rule G should be brought into the position denoted in Fig. 3; that is to say, turn the circle round in its center until the side of the rule 75 G is parallel to the perpendiculars denoting the seams of the cloths; then the angle subtended between the inner edge of the rule E and the zero of the upper limb of the circle x or center line of the rule G will be the 80 complement of the angle required which in this case we find is (34°) thirty-four degrees; subtracting this from (90°) ninety degrees we have (56°) fifty-six degrees for the angle of the stay gore. Now on looking 85 in the tables in the double column of degrees above (45°) forty-five degrees, against (56°), we find 3 feet and 5 inches as the depth of C a Fig. 2, or the stay gore for each cloth.

As the foot of a jib for large vessels is seldom cut on a straight line but cuved as seen at A f B, Fig. 2, or in nautical language "with a sweep," the mode I adopt for finding the gores on the foot for each cloth 95 is thus described. Bring the ruler I into the position denoted by the dotted lines in Fig. represent the required shape of the jib, the pass through the point f. Then that portion of the curve of the ruler between h and f 100 will exhibit the sweep of the foot.

The ruler I is not formed with any particular curve but such a one may be adopted as will answer for different sails—or instead of one ruler we can employ two or 105 three of different curves according to the

pleasure and taste of the sailmakers. The ruler I being in the position above mentioned, clamp it by the nut —k—. Next we remove the rulers E F G and circle x 5 leaving the rulers D and I. First we wish to obtain the angle on which to cut the gore, A g Fig. 2, or the angle made by a chord A g with a line drawn through g parallel with D B. We move the ruler D, downward 10 until its upper edge coincides with the intersection of the line between the cloths 1, and 2, Fig. 3 and the upper curve of the ruler I. This intersection corresponds with the point g Fig. 2. Then the fiducial edge 15 of the index -i— of the ruler D will denote the number of degrees in the angle required which in this case is (19°). Then looking in the table we find in column No. 1, against (19°), in the adjacent column, the number 20 10 or ten inches as the depth of the first gore. Then on cutting the first and the stay gores of the first and second cloths, in the manner before mentioned we measure off the length h g Fig. 2, of the after selvage 25 of the second cloth by applying it to the free selvage of the first cloth. Our next operation is to obtain the angle of g h. Move the ruler D a short distance upward until its upper edge coincides with the point 30 h or end of the divisional line between the second and third cloths. By inspecting the semicircle f g h Fig. 2, we thus have the angle made by a straight line drawn from A to h Fig. 2, and a line through the point 35 h parallel D D, say equal to (18°). Now looking in the table double column No. 2 against (18°) we find 18 inches, as the depth of gore for two cloths. Then (18-10) eighteen minus ten leaves 8 inches as the 40 depth of the gore of the second cloth.

For the foot of the third cloth we move the ruler D upward as before, and read off the angle between the points A i and an imaginary line through i Fig. 2, par-45 allel to D B which in this case suppose to be (16°). Against (16°) in No. 3, denoting the third cloth, we find 24 inches as the whole depth of gore. Therefore subtracting from the same 18 or the sum of the depths 50 of the first and second cloths we have (6) as the depth of gore of the third cloth. Then as in Fig. 4, as we are to form the foot of the third cloth, which we have already shaped on the angle of the foot g h of the 55 second cloth, we must set off two inches from g to l. Then l m will be equal n i or six inches. Cut from h to l and we obtain the true shape of the foot of the third cloth. We continue, in a similar manner for the re-60 maining cloths having previously made our calculations of the differences g l for each cloth; if we are correct in setting off and cutting the slope A g of the first, we shall Γ

find no difficulty in proceeding with the rest and thus we are enabled to cut a jib with 65

or without a sweep on the foot.

I now proceed to exhibit the application of the scales to finding the gores on the head, foot, and mast or fore leach of a trysail of the following dimensions.

Hoist on the trysail mast=24 feet. Length of trysail on the foot=37 feet. Do Do. head=27 feet.

Do of diagonal=39 ft. 6 inches.

Do after leach=37 feet.

The rulers will be arranged as exhibited in Fig. 5; and in order to dispose them as therein represented, we first lay on ruler —C— the length from k to h corresponding to the diagonal which would be seven inches 80 and nine-tenths of an inch. Through the division hole we insert the projecting pin y, Fig. 1, for the intersection of the rulers E and F, Fig. 5. Then lay off g h on ruler E equal to five inches, and four tenths of an 85 inch, which gives us the length of the trysail on the head; also lay off g k equal to seven inches and four-tenths of an inch corresponding to the after leach. Clamp C and E in this position. Next set off h i on F 90 equal to four inches and four tenths of an inch and i k on D equal to seven inches and four-tenths of an inch. The space g h i kcircumscribed by the rulers will thus exhibit the exterior of the trysail while the 95 card or ruled paper on the board will show the number of cloths in the same.

The gore on the head is found by bringing the circle a and ruler G into the proper position denoted in Fig. 5, when we shall 100 find that the ruler E will cut on the graduated circle x the angle of the head gore which in this particular instance will equal (16°). Then looking in the tables under double column No. 1 we find against (16°) 105 8 inches as the depth of gore required.

The gore on the foot is determined by the angle which the index of the ruler D indicates on the graduated semicircle. e' f' g'which in this particular case is twelve de- 110 grees (12°) against (12°) in the tables we find 6 inches as the depth of the foot for each cloth.

The gore on the mast or fore leach is determined by the angle which the inner edge 115 of the ruler F' cuts on the graduated circle x, which is the complement of the angle of gore. In this case the gore angle will equal (65°) and the depth of the gore will equal 5 feet.

The next sail in order is the square mainsail Fig. 6, and we now proceed to determine the gore on the side leaches and roach of the foot by the application of the scales and tables. As on inspection of Fig. 6 it 125 will be perceived that both sides of this sail

2,790

are alike, or A E F C equals D B E F we have only to project one-half by the scales. In this case it will readily be seen from the foregoing explanation, that by laying off 5 on the ruler E, from its point of junction with the ruler F, half of the length of the head of the sail or E B, and placing the edge of said ruler perpendicular to the lines of canvass, or to the edge of A, and also setting 10 up F E on ruler A and B D on ruler F we can obtain the angles for the side gores; and also by reversing the ruler I so as to form the roach of the foot or F D, we can obtain the angles of the gores of the feet of strips 15 or cloths, in a similar manner and by similar principles to those heretofore described in the explanation of the mode of finding the sweep of a jib. As all this will be easily understood by any sail maker, from the principles heretofore explained, it is unnecessary to go into any more particular description of the same. As a straight ruler H divided as seen in Fig. 1, and having screws and nuts a^3 b^3 is sometimes con-25 venient, during the operations of determining the angles and dimensions of other sails, and may be used according to the pleasure of the sail maker, I have added one to my collection of scales, but I do not consider it 30 as embraced in my main collection, but merely secondary to the same. Having herein-above explained the con-

struction of my mathematical scales, and

tables together with their practical applica-

35 tion, I now proceed to specifically point out, |

and circle x, the whole constructed, ar-40 ranged, graduated and operating together, substantially in the manner above mentioned and described, for the purpose of determining the angle of the gores on the head, foot and leaches of different sails as herein above 45

such parts thereof I claim to be my inven-

1. I claim, the scales A and B, in com-

bination with the scales C D E F, ruler G,

explained.

tion—

2. I also claim, the combination, with the above specified parts of the ruled table or card e' f' g' h', constructed and arranged substantially as above described for the purpose of determining the number of breadths or cloths of canvass in a sail, in the manner

herein-before explained.

3. Furthermore, I claim, the curved ruler I, constructed and arranged substantially as 55 above described, in combination with the ruled table or card e' f' g' h' and the scales A and D, for the purpose of determining the angles of the gores of the roach or sweep of the foot of a sail, in the manner herein before explained.

In testimony that the above is a true description of my said invention and improvement I have heretofore set my signature this fifth day of December in year eighteen hun-

dred and forty.

JOHN DOMINIS.

Witnesses:

WM. JARRETT,
WILLIAM LADD.