



J. Pfaff
Flute.

N^o 17,054.

Patented Apr. 14, 1857.

Fig. 2.

Fig. 1.



Witnesses

Henry Howson.
William W. Allen.

UNITED STATES PATENT OFFICE.

JOHN PFAFF, OF PHILADELPHIA, PENNSYLVANIA.

FLUTE.

Specification of Letters Patent No. 17,054, dated April 14, 1857.

To all whom it may concern:

Be it known that I, JOHN PFAFF, of the city of Philadelphia and State of Pennsylvania, have invented certain new and useful
5 Improvements in Flutes; and I do hereby declare that the following is a full, clear, and exact description of the same, reference being had to the accompanying drawing and to the letters of reference marked thereon.
10 My invention consists in placing the mouth-pieces of flutes at right angles, or thereabout, to the stems or bodies, in order that greater convenience may be afforded to the players, and the distortion of arms, fin-
15 gers, and neck required in playing upon flutes of the ordinary construction, may be avoided.

In order to enable others skilled in the art to make and use my invention, I will now
20 proceed to describe its construction and operation.

On reference to the drawing which forms a part of this specification Figure 1 is a front view of a portion of a flute with my
25 improvement attached thereto; Fig. 2, a side view, and section through the mouthpiece.

A is the body of the flute, which may be of the ordinary construction, and furnished with any of the systems of keys at present
30 in use. Into the top of the body I insert a bent tube B, the top of which is straight and projects at right angles, or thereabout to the body A. Onto the projecting portion of the tube B is fitted another tube C, which with
35 its hole *a* forms the mouthpiece. The tube C can be turned to any position desired by the player.

D is an adjustable stop common to all flutes.

In playing upon the ordinary flute it is 40 necessary to turn the head partially on one side, and to maintain the arms in an unnatural position, causing distortions and strains which have been found to affect the chests of players, and more especially of be- 45 ginners. The fingers and wrist too have to be stretched to an inconvenient extent. By my arrangement of mouth piece as regards its position with the body of the flute, the player is enabled to hold the instrument in 50 the same manner as he would hold a clarinet or flageolet, thereby obviating the above mentioned inconveniences. The bent tube B instead of having any injurious effect on the tone of the flute, actually improves it both as 55 regards clearness and volume.

I do not desire to confine myself to the exact form of bent tube shown as the same may be modified and ornamented in various ways without altering the desired result. 60 But

What I claim and desire to secure by Letters Patent is—

The placing of the mouth pieces of flutes at right angles or thereabout to the stems or 65 bodies of the same for the purpose specified.

In testimony whereof I have signed my name to this specification before two subscribing witnesses.

JOHN PFAFF.

Witnesses:

HENRY HOWSON,
C. CHAMBERS, Jr.