


Sheet 1-2 Sheets.

M. D. Whipple.
Spinning Mach.

N^o 18,529.

Patented Oct. 27, 1857.

Fig: 1.



M. D. Whizjule.
Springing Mach.

N^o 18,529.

Patented Oct. 27, 1857.

Fig:5.




Fig. 4.





Fig: 2.



UNITED STATES PATENT OFFICE.

MILTON D. WHIPPLE, OF CHARLESTOWN, MASSACHUSETTS, ASSIGNOR TO ALFRED B. ELY,
OF NEWTON, MASSACHUSETTS.

MACHINERY FOR SPINNING FLAX AND HEMP.

Specification of Letters Patent No. 18,529, dated October 27, 1857.

To all whom it may concern:

Be it known that I, MILTON D. WHIPPLE, of Charlestown, in the county of Middlesex and State of Massachusetts, have invented certain new and useful Improvements in Machinery for Spinning and for Laying Up Hemp and Similar Fibrous Material; and I hereby declare the following to be a full, clear, and exact description of the same, reference being had to the accompanying drawings, making part of this specification, in which—

Figure 1 is a view of an improved machine for spinning hemp, flax, &c., the apparatus for laying up the spun thread being shown with it as the same drawing motion is applied to both. Fig. 2 is a longitudinal vertical section through the same on the line *x x* of Fig. 3. Fig. 3 is a transverse vertical section on the line *y y* of Fig. 2. Figs. 4 and 5 details to be referred to.

The object of my present invention is to obtain a machine by which I can spin hemp, flax, and similar fibrous material directly from the hank without the necessity of first forming it into a sliver, thus doing away with the drawing rolls and much of the expensive part of the operation of spinning, and substituting therefor a drawing movement that more closely resembles that of hand spinning, and which allows the twist given by the spindle to follow up close to the hank from which the fibers are drawn. As this same drawing principle is applicable to laying up the spun thread or forming rope I have shown the manner in which it may be applied to such purpose, as well as an improved method of laying up such strands by rolling them together between two disks as the twist is laid in and thus compensating for any difference in the thickness of the strands.

In the drawings A. is the frame of the machine on top of which is secured in suitable bearings the shaft B to which power is applied through the pulley C on one end of it. A belt *a*. from another pulley at the other end of the shaft gives motion through a pulley L (Fig. 2) to a shaft D, which carries a long drum E from which belts communicate motion to the spindles F and G. and to other parts of the machine as will be explained. A pulley H on the shaft D and

belt *b* gives motion to the pulley I, on the cam shaft K, which has its bearings at the two sides of the frame A, and extends across the machine. The belt *c* over a smaller pulley attached to the inner face of the pulley I gives motion to the pulley M that is carried on a short shaft having its bearing on the top piece of the frame A.

Attached to the outer face of the pulley M, is an eccentric cam N, which operates a lever O, pivoted at one end on the shaft P; this shaft is supported in bearings on two of the uprights or legs of the frame A, and extends across from one side to the other of the frame. The lever O is held in contact with the cam N by a spring *d*, and has pivoted to it near the middle of its length a pawl *e*, that operates a ratchet wheel Q, secured to the shaft P. A retaining pawl *f* for this wheel is pivoted to the side of the frame A. The shaft P carries two heart shaped cams R, (one of which is seen in Fig. 2.) These cams operate two levers S, pivoted at *g*, to the inside of the longitudinal ties of the frame A. Through these levers is operated a gate T, sliding up and down in the frame A. Stirrups *h*, attached to the gate T, embrace the spindles F and G, and as the levers S, are vibrated the spools on these spindles are raised and lowered to regulate the winding on. The cams R perform another office which will now be explained.

A box V, for the reception of the hank is formed of a middle partition 1 to which is hinged on either side two sides or flaps 2 which are supplied with teeth *i* (see Fig. 1). These side flaps are opened and the hank is laid longitudinally over the partition 1, with the bight projecting from the front of the box. The flaps 2, are then closed down over it, and the box is placed in a trough V, into which the box fits. This trough is attached at its rear end by a single screw *h*⁵, passing through the bottom of it to a bar W, that extends across the rear end of the machine and is pivoted at each end to the frame A. This trough also rests near the middle of its length on a short standard *k*, attached to a bar X, the two ends of which slide up and down in grooves in the inner sides of the frame A. This bar rests on the two cams R and as they are revolved the trough V, is

vibrated vertically a short distance, the bar W, swinging on its pivots; the trough V, is also caused to vibrate horizontally on its pivot h^5 in the following manner. A bar Y, (Figs. 2 and 3) extends across the machine and is allowed to play longitudinally through slots in the sides of the frame A. One end extends through the frame and is held in contact with a cam l , on the inner face of the pulley M, by a spring m , attached to the rod and to the inside of the frame A. A rod n rises from the rod Y up attached to the frame and to the upper part of the block B'. These cams are so arranged that as the shaft K, revolves, the bars A', B' alternately approach to and recede from each other.

The bar A' is furnished with two pairs of nippers, one pair marked 5, near one end of the spinning apparatus and one pair marked 6 near the other end for the laying up apparatus. They are formed of a stationary jaw t , fixed firmly to the bar, and a movable jaw u pivoted to the bar, the movable jaws of each pair being connected together by a rod v so that the vibration of one shall move the other. A block a' on one of these movable jaws is held in contact with the side of the cam 3, by a spring w attached to the other jaw u and to the side of the frame. The cam 3 is cut away on its side to the proper form (as seen dotted in Fig. 3). Thus these nippers are opened and shut by the revolution of the shaft K. A similar pair marked 7 is attached to the bar B' for the laying up apparatus, and a pair of draw nippers of a different construction marked 8 are attached to the other end of this bar for the spinning apparatus. This latter pair is formed of two bent arms c' d' (Figs. 1 and 5,) pivoted together at e^3 , to the back of the bar B'. The arm d' is furnished with a sheet metal jaw e' which shuts into a double sheet metal jaw f' attached to the arm c' . The edge of each of these jaws is notched, forming when they are together a lozenge shaped hole which is enlarged and contracted by the vibration of the arms c' , d' ; this vibration is effected by the shaft K, in the following manner: A lever E' is pivoted at g' to the back of the bar B'. A small block h' attached to the lower end of this lever is held in contact with the side of a cam q , on the shaft K, by a spring h^4 attached to the upper end of this lever and to the bar B'. A flat rod i' connects the upper end of the lever E', to the lower branch of the arm c' and a flat rod k' , with a slot at l' connects the other end of the same lever to the lower branch of the arm d' . A spring m' is attached to the rod k' and to the lever E'. This method of connecting the lever E', to the arm d' allows the bite of the jaws e' — f' to accommodate

itself to the varying quantity of fiber drawn through them. A rod n' is attached to the arm c' and to the movable jaw of nipper 7 which is thus vibrated with the arm c' . Thus as the shaft K is revolved the blocks A', B', are vibrated toward and from each other and the two pairs of nippers attached to one bar are opened and shut in alternation with the two pairs on the other bar.

To insure the drawing out from the hank of a sufficient quantity of fiber to make the yarn being spun uniform, I have adopted the following device: A stout bar F', extends across the machine and is pivoted at o' to the inner side of the frame A. To this bar at one end is attached an arm G', which is formed in two parts hinged together at r' , near the middle of its length. The other end of this arm is attached to a bar H' (Fig. 3) which is pivoted at one end to the frame A and at the other to a standard I' rising from the middle cross brace of the frame. The arm G' is held by a spring K' in contact with a cam 10, on the shaft K, by the revolution of which the elbow at r' is depressed and the two bars F', and H', are vibrated. From the bar H', rise two standards p' which carry at their upper ends a shaft q' having secured to its outer end beyond one of the standards a pulley s' to which is attached a cord t' , which passes over the pulley and is attached at its other end to the part 3 of a treadle L' seen enlarged in Fig. 4, which is attached to the bar F'. This treadle is formed of three parts, No. 1 being rigid, and vibrating with the bar F. No. 3, is pivoted at u' to No. 1, and has attached at its outer end the cord t' . No. 2, lies between 1, and 3 and is pivoted to No. 1, and when in the position shown in the drawings wedges them apart so that the outer end of No. 3 will not be caught by the projecting lip v' , of a block w' attached to the outer end of No. 1, but when No. 2, is raised by a rod x' in a manner which will be explained the parts No. 1, and No. 3 spring together and No. 3, is caught under the block w' and it is vibrated with No. 1, by the bar F', thus drawing down the cord t' and causing the shaft q' to revolve a portion of a circle in the direction of the arrow Fig. 2. An elastic belt y' (Fig. 3,) attached to the shaft and to the bar H', turns the shaft back again when the cord t , is slacked up.

The shaft q' carries a metallic disk z' with a single hooked notch or tooth in its periphery, which whenever this shaft is revolved by the cord t' is thrown up into contact with the fibers being drawn from the hank, and as the block H' is vibrated as before explained, the hook in the disk z' draws out more of the fibers from the hank and increases the quantity being drawn out by

the draw nippers 8. That this may only occur when the nippers 8 are not drawing out sufficiently fast, the following device is used for regulating this part of the operation: A lever a^2 is pivoted to the top of the arm d' of the nippers 8. To the outer end of this lever is pivoted the rod x' , the other end of which is pivoted to the part 2 of the treadle L' . To the top of the arm c' of these nippers is attached a set screw b^2 the end of which projects a short distance toward the arm d' . The lever a^2 is allowed to vibrate freely and the part No. 2 is carried with the treadle L' , but whenever the amount of fiber passing through between the jaws f' and e' of the nippers 8 becomes reduced below what is required, it allows the jaws to come closer together and the short end of the lever a^2 is caught under the end of the screw b^2 and the lever is prevented from vibrating, and the wedge No. 2 of the treadle L' is held up by the rod x' and the parts No. 1 and No. 3 are allowed to spring together, when No. 3 is caught under the block w' and is vibrated with the part No. 1 by the bar F' . This draws down the cord t' and revolves the shaft q' as before explained and the hook on the disk z' is thrown up among the fibers and this motion of the disk in connection with the vibration of the bar H' draws out some more of the fibers from the hank and increases the quantity grasped between the jaws of the nippers 8, which prevents them from coming so close together as to let the end of the lever a^2 catch under the set screw b^2 when the wedge No. 2 of the treadle L' drops into the position shown in Fig. 4, and the part No. 3 is held off so that it does not catch under the block w' and the treadle L' vibrates without drawing down the part No. 3, which is left free to vibrate on its pivot u' . The shaft q' is now revolved a part of a turn in the opposite direction by the retraction of the elastic band y' and the hook of the disk z' is thrown down (as in Fig. 2) out of the way of the fibers and although the bar H' continues to be vibrated as before the fibers are only drawn out by the action of the nippers 8.

The laying up part of my improved machine will now be described.

The spools 1, 2, 3, containing the spun yarn are secured to the heads A^2 , B^2 , C^2 , which are carried on a standard D^2 rising from the end of the frame A and are revolved all in one direction by a band d^2 leading over the drum E. The ends of these yarns are lead through a hole in a metal plate or guide e^2 (Figs. 2 and 3) which keeps them in contact with each other, thence between two metallic disks f^2 — z^2 , thence between the draw nippers 7 and 6, thence over a guide pulley O' on the shaft B, to the spindle G, where the laid up cord or rope is wound up on a spool on this spindle. The

nippers 7 and 6 are opened and shut and vibrated to and from each other by the revolution of the shaft K, as before explained. The disks f^2 , z^2 , are carried on the ends of two short shafts h^2 i^2 which are supported on standards l^2 rising from a block P' which is attached at one end to the side of the frame A and is supported at the other end by the upright I' . These shafts h^2 , i^2 , are revolved in opposite directions by bands leading over pulleys on these shafts and over a drum Q' which is driven by a band m^2 leading over the drum E. The shaft h^2 is allowed to play longitudinally in its bearings in the standards l^2 and the disk f^2 is pressed toward the disk z^2 by a spring n^2 secured to one of the standards l^2 . Thus these disks accommodate themselves to any variation in the thickness of the cord or rope being laid up at the same time that their surfaces revolving in opposite directions in contact with the cord as the twist is laid in, compensates in a measure for the difference of thickness of the yarns or strands and prevents the larger strand from winding around the smaller ones, as it is apt to do when laid up in the customary manner.

That the twist given to the yarn or cord by the spindles F and G may pass over the guide pulleys R' , O' , on the shaft B, and run up toward the nippers, each of these pulleys is furnished with one or more inclined wires or staples i^3 which are secured in the groove of the pulley and lie diagonally across it. As the pulley revolves, these inclined staples or teeth act upon the twist and pass it over the pulley, and the pulley does not stop the twist as it would do if the staples i^3 were not placed in the groove. Instead of these staples a diagonal notch or groove may be cut across the groove of the pulley. This will have a similar effect in passing the twist over the pulley.

Operation: The hank of hemp, flax, or other fibrous material to be spun, is placed in the box U, as before described, and the fibers are drawn from the bight or middle of it over the disk z' through between the jaws of the nippers 8, then through between the jaws of the nippers 5, thence over the guide pulley R' on the shaft B, to the spindle F, which is revolved as before explained. By this spindle the twist is given to the thread, and by the vibration of the blocks A' B' and the opening and closing of the nippers 5 and 8 the fibers are drawn out from the hank and the twist is allowed to run up close to the hank, as it could not do if draw rolls were used instead of these draw nippers. I thus avoid the necessity of forming the fibers into a sliver by means of extra machinery before it is spun. The operation of the hook on the disk z' as explained keeps the amount of fibers drawn out by the nippers 8, uniform. The spun yarn thus

formed is taken from the spindle F to the
laying up apparatus, the spools being at-
tached to the revolving heads A², B², C²,
from which the threads are led through the
5 guide e², between the disks f² z², through
the nippers 7 and 6, over the guide pulley O'
to the spindle G', by which the twist is laid
in and the finished cord or rope is wound
up. The draw nippers 7 and 6 are opened
10 alternately and allow the twist of the cord
to run up to the guide e² of the disks f² g²,
rolling in the twist as before explained and
compelling the various strands to place
themselves in a uniform position around the
15 central axis of the cord or rope, which will
enable me to produce a smoother and
stronger article than has heretofore been
possible where the strands were allowed to
adjust themselves around the axis of the
20 article being laid up, when a variation in
the thickness of either strand would cause
an irregularity in the twist and consequently
in the strain brought upon the different
strands when traction was applied longi-
25 tudinally to the rope.

What I claim as my invention and desire
to secure by Letters Patent is—

1. I claim the device herein employed for
regulating the amount of fiber drawn from
the hank by the size of the yarn, consisting 30
essentially of the lever a², and screw or stop
b² attached to the draw nipper 8 with its
immediate connections, and the hook disk z'
operating in the manner substantially as set
forth. 35

2. I claim the vibrating draft nippers, op-
erating in the manner substantially as set
forth whereby the twist is allowed to run up.

3. I claim the vibrating hank holder U
constructed and operating substantially as 40
described.

4. I claim the inclined wires or teeth on
the guide pulley O' R' operating in the
manner and for the purpose substantially as
set forth.

MILTON D. WHIPPLE.

Witnesses:

THOS. R. ROACH,

P. E. TESCHEMACHER.