

J. Moulson,
Key-Hole Guard.
N^o 21,616. Patented Sep. 28, 1858.

Fig. 1.





Fig. 2.



UNITED STATES PATENT OFFICE.

JOHN MOULSON, OF PHILADELPHIA, PENNSYLVANIA.

KEYHOLE-STOP.

Specification of Letters Patent No. 21,616, dated September 28, 1858.

To all whom it may concern:

Be it known that I, JOHN MOULSON, of the consolidated city of Philadelphia and State of Pennsylvania, have invented a new
5 Keyhole-Stop for the Prevention of Depredations on Door-Locks; and I do hereby declare that the following is a full and exact description thereof, reference being had to the accompanying drawings and to the letters of reference marked thereon.
10

The nature of my invention consists in the structure and combination of two or more metallic pieces intended, in conjunction, to fill a key hole in a door, after the
15 lock has been locked, which I therefore call a "key hole stop" which must be used in conjunction with a padlock or its equivalent for the purpose of preventing the introduction of any unwelcome key or other instrument therein to unlock said door lock.
20

To enable others skilled in the art to make and use this my invention I will proceed to describe its construction and operation.

I construct two or more pieces of metal, the
25 first A, Figure 1, a female or groove piece, consisting of a piece of sheet iron or other metal (preferably tapered a quarter of an inch on the long sides) about four inches long, from *a*, to *b* Fig. 1, or to correspond
30 with the thickness of the door and lock to be secured, formed with a channel or groove *c*, *d*, throughout its whole length which may be formed by doubling the metal lengthwise in the middle, leaving a space of one-sixteenth of an inch or more between the sides
35 (when bent and closed) sufficient to receive freely the male piece B Fig. 2 within the groove *c* *d*, or it may be made of cast metal of the same shape; the width of this piece
40 A on its wide end *a*, is to be about three-eighths of an inch, tapering down to one quarter of an inch at the narrow end *b*, on the bottom of which end *b* is to be made a lug *e* or projection downward and which
45 may preferably be inserted in the groove immediately above it of an eighth of an inch and as much in width and thickness to prevent the withdrawal of this piece from the lock, when the male piece B has been introduced into the groove *c*, *d*, the tapering
50 of this piece A to nearly correspond with the depth of the lug *e*. Near the end *a*, is to be made an aperture *f*, through both sides about a quarter of an inch in diameter, or
55 sufficiently large to admit the introduction

of the shank of a padlock through it when adjusted in the key hole, and the piece B Fig. 2 introduced into the groove *c*, *d*, so that both pieces will be held in place and be secured by the padlock.
60

The male piece B Fig. 2 consists of a flat plate or piece of metal preferably one-eighth of an inch longer from *c* to *d* than the piece A Fig. 1 and of about one-sixteenth of an inch in thickness or enough to nearly fill
65 the groove *c*, *d*, Fig. 1, and of equal width at the ends *g* and *h*, but about the eighth of an inch wider from *i* to *k*, than the widest part *c* to *g* of the grooved piece A when placed therein, and is preferably provided
70 with a lug *l* or projection on the lower side at the end *g* of one-eighth of an inch deep and as wide, intended for a stop when sliding this piece into the groove *c*, *d*. There is also near the same end *g* an aperture *f* to
75 be made to correspond in position with the apertures *f*, Fig. 1 so as to receive the shank of a padlock which being introduced when these two pieces A and B are placed in the key
80 hole, first the piece A with the lug end *b* foremost, and then the piece B with the plain end foremost, placed within the groove *c*, *d*, and passed in until the lug, *e*, drops down below the bottom of the key hole and
85 all the apertures *f* *f* correspond, so that the shank of a padlock or its equivalent can be passed through all the apertures *f* *f* holding, with the lug, both pieces in place, preventing the introduction of any instrument to
90 unlock the door lock or the withdrawal of this stop on account of the lug, *e*, until the removal of the shank of the padlock and the withdrawal of this "key hole stop."

In order to adapt this mechanism to a variety of sized key holes, the male pieces
95 B must be of sufficient widths and thickness, in combination with the female piece A to fill the key hole of whatever size or depth; and it is intended to provide several male
100 pieces B with each female piece A the length of both and all the pieces to suit the depth of the key hole or thickness of the lock and door to be secured.

The sizes and dimensions here given are not arbitrary, but may be varied to suit the
105 size and depth of any key hole.

What I claim as my invention and desire to secure by Letters Patent is—

The construction of a "key hole stop" consisting of two pieces of metal, one to slide
110

into the other, which when introduced into
a key hole, first the female and then the
male piece, in conjunction with a ring on one
piece, and a padlock or its equivalent
5 through both pieces, all combined as de-
scribed, or their equivalents, will fill the key
hole and effectually prevent depredations on

locks by preventing the introduction of any
unwelcome key or other instrument therein.

JOHN MOULSON.

Witnesses:

WILLIAM SNIDER,
Z. SNIDER.