



E. ROUGHTON

Carriage-Spring.

No. { 556,
31,560. }

Patented Feb 26, 1861.



Witnesses

C. M. Alexander
a a Graham

Inventor

E. Roughton

UNITED STATES PATENT OFFICE.

E. ROUGHTON, OF FROSTBURG, MARYLAND.

ARRANGEMENT OF CARRIAGE-SPRINGS.

Specification of Letters Patent No. 31,560, dated February 26, 1861.

To all whom it may concern:

Be it known that I, E. ROUGHTON, of Frostburg, in the county of Allegany and State of Maryland, have invented certain
5 new and useful Improvements in Springs for Carriages and other Vehicles; and I do hereby declare that the following is a full, clear, and exact description of the same, reference being had to the accompanying drawings and to the letters of reference marked
10 thereon.

The nature of my invention consists in constructing and arranging vehicle springs in the manner hereinafter set forth.

15 In the annexed drawings Figure 1 represents a side view of buggy body with springs attached. Fig. 2 is an end or back view of same.

20 In the figures A represents the body of the vehicle; B, B, the head blocks and C, the connecting shaft or bar between them.

25 *a, a*, represent two rods which are secured perpendicularly to the head blocks near the ends of each—the head blocks being between the rods and also between two plates *c, c'*, which secure the rods, as well as the springs to the head blocks.

30 To the four corners of the vehicle are secured the projecting bars *d, d*, which rest upon the springs and which are provided with holes through which the rods *a, a*, pass.

35 *E*, represents a band of metal which passes over the springs as seen in Fig. 2—the upper ends of the rods passing through and being attached securely to said band.

H, H, represent the springs which are

formed by taking a straight piece of steel and bending it until its two ends touch. These ends are then caught under the plate *c'*, and are there secured by bolts on the lower ends
40 of the rods *a, a*, or otherwise if desired. The tension of this spring may be increased by duplication as seen in Fig. 2, where two pieces are used. More may be used if necessary. The bars *d, d*, press upon the top of
45 the outer spring in the manner shown—said bars being allowed to slide freely over the rods *a, a*. Springs may be used between the bars *d, d*, and the band *E*, to prevent the body of the vehicle from jumping up when
50 passing over obstructions. In this manner a very cheap and easily constructed spring may be used and the four corners of the body of the vehicle will be supported alike.

Having thus fully described my invention
55 what I claim as new and desire to secure by Letters Patent is—

1. The employment of the bars *d, d*, the rods *a, a*, and the band *E*, arranged in the manner represented for the purpose of hold-
60 ing the body of the vehicle in position, and for shielding, and protecting the springs from strain substantially as set forth.

2. The combination of the springs *H H* with the bars *d, d*, rods *a, a*, band *E*, and
65 plates *c, c'*, the several parts being used as and for the purpose specified.

E. ROUGHTON.

Witnesses:

C. M. ALEXANDER,
A. A. YEATMAN.