


D. LIPPY.
Fruit Drier.

No. 48,570.

Patented July 4, 1865.



WITNESSES
Ther Fusch
Wm. Brown


INVENTOR
D. Lippay
per Munroe & Co
attorneys

D. LIPPY.

Fruit Drier.

No. 48,570.

Patented July 4, 1865.



Witnesses.
Thos Tusch
W. Hewin

Inventor
D. Lippy
per Munn & Co
attorneys

UNITED STATES PATENT OFFICE.

DAVID LIPPY, OF MANSFIELD, OHIO.

FRUIT-DRIER.

Specification forming part of Letters Patent No. 48,570, dated July 4, 1865.

To all whom it may concern:

Be it known that I, D. LIPPY, of Mansfield, Richland county, State of Ohio, have invented a new and Improved Fruit-Drying Device; and I do hereby declare that the following is a full, clear, and exact description thereof, which will enable others skilled in the art to make and use the same, reference being had to the accompanying drawings, forming part of this specification, in which—

Figure 1, Sheet No. 1, is a vertical section of my invention, taken in the line *xx*, Fig. 2. Fig. 2, Sheet No. 2, is a vertical section of the same, taken in the line *yy*, Fig. 1.

Similar letters of reference indicate like parts.

This invention relates to a new and improved device for drying fruit; and it consists in a novel arrangement of a furnace, dampers, and drawers, as hereinafter fully shown and described, whereby fruit may be dried expeditiously and with but a small expenditure of fuel.

A represents a building, which may be of any suitable dimensions, and B is a furnace placed in its lower part and extending its whole length. This furnace may be constructed of iron or masonry. It is of less width than the building A, so as to allow a space, *a*, at each side of it, and it has a horizontal plate, C, a short distance above it equal in area to the top of the furnace, and another plate, D, is placed a short distance above C, the latter being provided with a register, E. The plate D does not extend the whole width of the house or building A, a space, *b*, being allowed at each side of it, as shown in Fig. 1.

F represents a series of drawers, which have slatted bottoms *c* and rest on cleats *d*. These drawers are somewhat less in width than the building A, so as to leave a space at each side of them, which spaces are provided with dampers G. The drawers at their centers are provided with dampers H. (See Fig. 1.)

I represents ventilators placed at each end of the building and provided with registers *e*,

and J represents registers placed in the ceiling K of the building, affording, when open, a communication with the loft or apartment above, the ends of which are provided with openings *f*.

The operation is as follows: The fruit to be dried is placed in the drawers F, and a fire being kindled in the furnace B, the heat ascends, the plates C D breaking the heat or shielding the lower drawer from it. By opening all of the dampers G H the heat ascends upward, as indicated by the arrows 1, and by closing the dampers G and opening the register E the heat will ascend upward through the centers of the drawers only, and by closing the dampers H the heat will ascend upward by the sides of the drawers. Thus the fruit may be uniformly dried throughout by regulating the dampers, as described. The ventilators I are opened to admit of the escape of steam. They are closed when all the steam has escaped from the building. An excess of steam is prevented by opening the registers J.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

1. A series of drawers, F, provided with slatted bottom *c* and dampers C, and arranged with dampers H at their sides, substantially as and for the purpose specified.

2. The furnace B, having two plates, C D, above it, one of which, D, is provided with a register, E, all being arranged in connection with the drawers and dampers to operate as and for the purpose set forth.

3. The ventilators I applied to the building A, and used in connection with the furnace drawers and dampers, substantially as and for the purpose set forth.

4. The combination of the furnace drawers, dampers, and ventilators, all arranged within a building to operate in the manner substantially as and for the purpose set forth.

DAVID LIPPY.

Witnesses:

R. VAN B. FINFROCK,
JOHN MELEY.