

## J.H.F.Etcher


Bed Bottom,


Nº54,879,


Patented May 22, 1866.











Witnesses: Lawwe N. Piper. George Andrews Inventor:
James H Fletcher.

By his attorney, Each

## United States Patent Office.

JAMES H. FLETCHER, OF LOWELL, MASSACHUSETTS.

## IMPROVED BED-BOTTOM.

Specification forming part of Letters Patent No. 54,879, dated May 22, 1866.

To all whom it may concern:

Be it known that I, James H. Fletcher, of Lowell, in the county of Middlesex and State of Massachusetts, have invented an Improved Bed-Foundation; and I do hereby declare the same to be fully described in the following specification, and represented in the accompanying drawings, of which—

Figure 1 is a top view; Fig. 2, a side elevation of it. Fig. 3 is a transverse section, and Fig. 4 a longitudinal section taken through its middle. Fig. 5 is a transverse section taken through one of its cross-bars, and the springs

for supporting it and the slats.

In the drawings, A denotes a rectangular frame provided with two cross-bars, B B, arranged within it. Each of such bars at its two ends extends into mortises a a, made in the side bars, b b, of the frame. Furthermore, each of the said bars B B not only rests at or near its opposite ends in two springs or blocks, c c, of india-rubber placed on the bottoms of the said mortises, but is provided with a series of vertical notches, d d d, made down in it from its upper surface, such notches being at equal distances asunder, and for the reception of a series of spring-slats, C C C, arranged within and lengthwise of the frame A. In

every one of the notches of each of the bars B B is a spring or block, e, of india-rubber, on which the slat placed in such notch rests.

The several slats are connected by flexible bands D D, which extend across the frame  $\Lambda$ , are affixed to its two side bars and to each of the slats, and serve to prevent the slats from being displaced from the notches of the crossbars.

The bed-foundation so made is simple in construction, efficient in operation, and easy to a person while on a bed or mattress supported by it.

I claim—

The said improved bed-foundation, or combination and arrangement of the frame A, with its mortises a a a a and india-rubber springs c c c c, the cross-bars B B, with their series of notches d d, and the series of slats C C C, with their supporting springs e e e, or the same and the holding-bands D D, the whole being substantially in manner and for the purpose specified.

JAMES H. FLETCHER.

Witnesses:

G. H. WASHBURN,

R. H. Eddy.