17.5.7001E1,

Molasses Pitcher,

Patented Sent.3, 1867.




Fig. 2

Witnesses:

Me Trevin Stellem Ethaser M. S. Roomey

er Municipal

Anited States Patent Pffice.

W. S. ROONEY, OF ALBANY, NEW YORK.

Letters Patent No. 68,532, dated September 3, 1867.

IMPROVED MOLASSES-CUP.

The Schedule referred to in these Xetters Patent and making part of the same.

TO ALL WHOM IT MAY CONCERN:

Be it known that I, W. S. Rooney, of Albany, in the county of Albany, and State of New York, have invented a new and improved Pitcher; and I do hereby declare that the following is a full, clear, and exact description thereof, which will enable those skilled in the art to make and use the same, reference being had to the accompanying drawings, forming part of this specification.

The present invention relates to a pitcher more especially designed for sirups, molasses, &c., and for house, hold and dining purposes; which pitcher is so constructed at its nozzle or spout as to prevent all drippings, after liquid has been poured therefrom, from running down the outside of the pitcher, and to convey them back into the body or reservoir of the pitcher. In the accompanying plate of drawings my improved pitcher is illustrated—

Figure 1 being a central vertical section of the same, and

Figure 2 a plan or top view, with the cover or lid raised or swung back.

Similar letters of reference indicate corresponding parts.

A, in the drawings, represents the body or reservoir portion of the pitcher, which in shape and design may be changed at pleasure, according as may be desired or found most suitable; B, the handle to the body A, and C the nozzle or spout thereto, through which the sirap or other liquid passes or is poured from the vessel. This spout or nozzle C is within the vessel or pitcher A, when its lid is closed, and in lieu of being attached to or forming a part of the upper edge a to the reservoir A, it is attached to or formed as a part of a plate or shelf. D, that is fastened to the vessel A in an inward inclined position, so as to allow whatever liquid may drip or fall thereon from the spout to pass back into the receptacle A, as in the use of the pitcher the liquid contained in it is poured therefrom.

I claim as new, and desire to secure by Letters Patent-

The construction and arrangement of the semicircular plate D, secured to one side of the pitcher A, in an inward inclined position, and provided at its centre and lower edge with the inclined spout C, as herein setforth for the purpose specified.

The above specification of my invention signed by me this 25th day of June, 1867.

W. S. ROONEY.

Witnesses:

John Crombie, William Crew.