


T. L. Goble.
Wagon-Jack.

N^o 76075

Patented Mar. 31, 1868.



Witnesses

W. C. Ashkett

J. A. Fraser

Inventor

T. L. Goble

per Munn & Co.
attorneys.

United States Patent Office.

T. L. GOBLE, OF ORANGE, NEW YORK.

Letters Patent No. 76,075, dated March 31, 1868.

IMPROVED WAGON-JACK.

The Schedule referred to in these Letters Patent and making part of the same.

TO ALL WHOM IT MAY CONCERN:

Be it known that I, T. L. GOBLE, of Orange, in the county of Schuyler, and State of New York, have invented a new and improved Wagon-Jack; and I do hereby declare that the following is a full, clear, and exact description thereof, which will enable others skilled in the art to make and use the same, reference being had to the accompanying drawings, forming part of this specification.

The figure is a side view of my improved wagon-jack.

My invention has for its object to improve the construction of my improved wagon-jack, patented April 30, 1867, and numbered 64,302, so as to make it more convenient and effective in operation; and it consists in the combination and arrangement of the various parts, as hereinafter more fully described.

A is the base-bar of the jack, which rests upon the ground, and to which the other parts of the jack are attached. To the forward end of the base-bar A is rigidly attached a short standard or post, B, to the upper end of which the forward end of the notched bar or rail C is pivoted. The rear end of the notched bar C is pivoted to the end of the eccentric-lever D, as shown in the drawing. E is a short standard or post, which should be a little longer than the stationary standard B, and the lower end of which is pivoted to the rear end of the base-bar A. To the upper end of the pivoted standard E is pivoted the eccentric-lever D, as shown in the figure.

In using the jack, by lowering the free end of the eccentric-lever D, the rear end of the notched bar C is raised, and, at the same time, the upper end of the pivoted standard E is moved forward, bringing the pivoting-point of the upper end of the said standard E beneath or in front of the pivoting-point of the rear end of the notched bar C, which locks the jack, and holds it securely in place until released by again raising the free end of the said eccentric-lever D.

I claim as new, and desire to secure by Letters Patent—

The combination of the base-bar A, stationary standard B, pivoted notched bar C, pivoted eccentric-lever D, and pivoted standard E, with each other, substantially in the manner herein shown and described, and for the purposes set forth.

The above specification of my invention signed by me, this 23d day of December, 1867.

Witnesses:

WILLIAM HEDGES,
CYRUS M. MERRIMAN.

T. L. GOBLE.