


*J. T. R. Yaggy,*


*Bag Holder.*

*No. 70,686.*

*Patented Apr. 14, 1868.*



*Fig: 1.*



*Fig: 2.*

*witnesses.*

*J. L. Coburn  
H. A. Ruppins*

*Inventor.  
Jacob Yaggy  
J. H. Yaggy  
by Coburn & Ruppins  
attys.*

# United States Patent Office.

JACOB YAGGY AND TOBIAS R. YAGGY, OF PLAINFIELD, ILLINOIS, ASSIGNORS  
TO TOBIAS R. YAGGY.

*Letters Patent No. 76,686, dated April 14, 1868.*

## IMPROVEMENT IN BAG-HOLDERS.

The Schedule referred to in these Letters Patent and making part of the same.

### TO ALL WHOM IT MAY CONCERN:

Be it known that we, JACOB YAGGY and TOBIAS R. YAGGY, of Plainfield, in the county of Will, and State of Illinois, have invented a new and useful Improvement in Bag-Holders; and we do hereby declare and make known that the following is a full, clear, and exact description of the same, reference being had to the accompanying drawings, and the letters and figures marked thereon, which form part of this specification.

Our said invention relates to a device for holding bags open and in an upright position, to enable the same to be readily filled with grain; and to enable those skilled in the art to understand how to construct and use our said invention, we will proceed to describe the same with particularity, making reference in so doing to the aforesaid drawings, in which—

Figure 1 represents a side elevation of our invention.

Figure 2 is a plan or top view of the same.

Similar letters of reference in the different figures denote the same parts of our invention.

A represents a vertical post, of suitable height and size, having two legs or braces C C, extending out upon that side upon which the bags are to be suspended, to form a sure and stable support, as shown in the drawings, while at the same time a space is left between them to allow the bag to hang free, and to permit the same to be removed readily from the apparatus when it is filled.

To the upper end of the post A, at d, a metallic ring, D, a little smaller than the mouth of a bag, is firmly secured in a horizontal position; said ring or rim being also firmly braced or supported by arms E, extending from the rim to the post A, as shown.

At the upper end of the said post A, upon each side thereof, are firmly secured iron bars a a, which have bearings to receive the ends of a pin or bolt, b, which turns in its bearings, as hereinafter set forth.

To said pin b, arms c are attached, which are also rigidly connected to an upper rim, F, which lies upon the rim D, but which can be opened or turned back upon its hinge when desired, as indicated by the dotted lines in fig. 1.

This upper rim is made wider than the lower rim, although its internal diameter is substantially the same, flaring outward and upward at the back, forming a sort of a hopper, to prevent the grain from falling over behind the bag, as it is being turned or shovelled in.

Upon the front edge of the hinged rim F are two ears f, in which the spindles e e, upon a lever, G, have their bearings, so that said lever may move about its spindles as upon a hinge.

The said lever G is provided with an arm, h, which passes beneath the rim D, its configuration or shape being such as to act as a clasp to hold the two rims firmly together, for the purposes hereinafter mentioned.

When a bag is to be arranged upon or in the bag-holder, the mouth is drawn up through the lower rim, the upper one being thrown back, as indicated by the dotted lines in fig. 1, and the edges of the bag are turned out over the rim D, when the rim F is brought down upon the edge of the bag, and the clasp G h is brought down beneath the rim D, thus firmly clasping the mouth of the bag between the rims D F, and keeping the same extended as desired.

When the bag is filled, the clasp h is removed from beneath the rim D, the rim F is thrown back, and the bag removed, and tied as desired.

Having described the construction and operation of our invention, we will specify what we claim, and desire to secure by Letters Patent.

We claim the combination of the post A, the legs C C, the rim D, the hinged rim F, and clasp G h, arranged and operating substantially as and for the purposes specified.

Witnesses:

ELTON WAGNER,  
J. D. SHREFFLER.

his  
JACOB X YAGGY,  
mark.  
TOBIAS R. YAGGY.