

A. D. Hoffman,

Conductors Punch.

No. 100,036.

Patented Feb. 22. 1870.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.





Fig. 5.



Witnesses.

G. H. Chapin
E. E. Gibson

Inventor.

Austin D. Hoffman

UNITED STATES PATENT OFFICE.

AUSTIN D. HOFFMAN, OF CHICAGO, ILLINOIS, ASSIGNOR TO HIMSELF AND
CHARLES H. MORSE, OF SAME PLACE.

IMPROVEMENT IN REGISTERING-PUNCH FOR RAILROAD CONDUCTORS.

Specification forming part of Letters Patent No. **100,036**, dated February 22, 1870.

To all whom it may concern:

Be it known that I, A. D. HOFFMAN, of Chicago, in the county of Cook and State of Illinois, have invented an Improved Conductor's Punch; and I do hereby declare that the following is a full, clear, and exact description thereof, which will enable those skilled in the art to make and use the same, reference being had to the accompanying drawings and letters marked thereon, making a part of this specification, in which—

Figure 1 is an elevation of my improved punch; Fig. 2, an internal view of the box-jaw, it being inverted and showing the opposite side to that shown at Fig. 1; Fig. 3, a broken view of the face-plate and dial removed from box-jaw at Fig. 2; Fig. 4, an elevation of the gearing inside of the box-jaw, removed to give a clear view of its construction; Fig. 5, a side elevation of the bell.

The present invention relates to an improved punch, which is designed to be used by conductors of cars, but more especially of street-cars; and its novelty consists in the arrangement whereby, when a punch is made to cut through a ticket or card, a bell will be rung, and the number of holes punched indicated, as the whole is hereinafter fully described.

A B represent the jaws of the punch, and C D the handles extending out therefrom, said jaws being jointed together at G in the usual manner of jointing similar tools. To the jaw A is hung a bell, F, and to its inner part near the joint G is fixed a punch, I, which is used to make holes through tickets, cards, &c., in the usual manner, except that the ticket in this case is put into a slot, X, in jaw A instead of between the jaws A B. The jaws are held the proper distance apart to allow a ticket to be put over the punch by means of a coil spring, Z, Fig. 1, inserted in one jaw, and made to bear against the other. The jaw B is provided with a rim and two face-plates, by means of which the following-described mechanism is placed in convenient position to indicate the number of holes punched, and also to ring a bell at the punching of each hole, as

shown at Fig. 4. *a b* represent journals, which have suitable bearings in the box-jaw B, and which support the following ratchet-gearing. A wheel, E, is fitted to journal *b*, and it is turned one notch every time the jaws A B are opened by means of a pawl, J, Fig. 2, which is fastened to the jaw A, and held to its work by means of a spring, K, Fig. 2. A pinion, S, Fig. 4, is also fastened to the journal *b*, and made to turn a wheel, V, which runs loosely on journal *a*, and carries with it a pinion, T, which drives a wheel, W, fitted loosely on the journal *b*. A pinion, R, is attached to the wheel W and drives a wheel, P, which is attached to journal *a*.

By means of this construction and arrangement, the wheel M drives the journal *b*, to which is fixed a hand or pointer, L, for indicating the number of holes punched up to twenty-five on its dial, Fig. 3, and the journal *a* is made to carry a hand, N, which indicates on its dial (at Fig. 2) the number of holes punched up to one thousand. A T-shaped shank, *f*, Fig. 1, supports a bell-hammer, *c*, and, as one end of the shank is pivoted to the jaw A, and the other to a sliding bar, H, the latter will, when the jaws are shut together, bring the hammer *c* against the bell F, the opposite end of said bar being slotted out, and operating on a pin, *g*, put into jaw B, allows the hammer *c* always to ring the bell when the hole is punched.

I claim and desire to secure by Letters Patent—

1. A card or paper punch, which is so arranged, by means of the jaws A B, handles C D, and gearing V T P M R S W, that the number of holes punched in a card or ticket may be registered by the hands N L on their dials, as set forth.

2. The combination of the jaws A B, bell F, handles C D, gearing V T P M R S W, hammer *c*, bar H, spring Z, and punch I, as and for the purpose set forth.

AUSTIN D. HOFFMAN.

Witnesses:

G. L. CHAPIN,
E. E. GIBSON.