
J. H. Hobbs,

Syrup Fitcher.

10. 102,124. Fatented Apr. 19. 1870.



Mitnesses alleghert, Abdurftel S. S. Hoff Inventor DY. Holloway 40 Atty

Anited States Patent Office.

JOHN H. HOBBS, OF WHEELING, WEST VIRGINIA.

Letters Patent No. 102,124, dated April 19, 1870.

IMPROVED SIRUP-PITCHER.

The Schedule referred to in these Letters Patent and making part of the same

To all whom it may concern:

Be it known that I, John H. Hobbs, of Wheeling, in the county of Ohio and State of West Virginia, have invented a certain Improvement in Sirup-Cups or Pitchers; and I do hereby declare that the following is a full, clear, and exact description thereof, reference being had to the annexed drawings making part of this specification, in which—

Figure 1 is a front elevation of my improved pitcher, showing how its discharge-nozzle is made a part of the same, and also how the covers may be

hinged thereto.

Figure 2 is a side elevation, showing the handle, the discharge-nozzle, with its aperture communicating with the interior of the pitcher, and also how the covers may be arranged to cover both the induction and eduction apertures.

This invention relates to that class of devices which

is known as sirup-pitchers; and

It consists of a new article of manufacture, consisting of such a pitcher, when made of glass or porcelain, as will be more fully described hereinafter.

A in the drawings refers to a pitcher, the general outline of which may be that shown in the drawings, or any other that will give it the required form and dimensions. It is to be made of glass or porcelain, and is to be furnished with a handle, in the usual manner.

Upon that portion of the body of the pitcher which is opposite the handle, there is to be formed a discharge-nozzle, C, the form of which is shown in the drawings.

This nozzle is to be formed upon the upper portion of the pitcher, and is to have an aperture through it for the discharge of the contents, which aperture is to be separated from the induction aperture by a bar of the material of which the pitcher is made, as shown in fig. 1, so that any covers which may be applied thereto may be hinged at a point directly on such bar, as shown in fig. 2.

This nozzle forms a part of the pitcher, as does also the bar, which separates it from the induction aperture, it being so constructed as not to project beyond the outer surface of the pitcher at its base, thus being protected from breaking by being brought in contact with anything against which the pitcher may be placed.

Having thus described my invention,

What I claim, and desire to secure by Letters Patent, is—

A sirup-pitcher, when made of glass or porcelain, and having its discharge-nozzle constructed and arranged as herein described, it being separated from the induction aperture by a bar, as shown, the same constituting a new article of manufacture, as and for the purpose set forth.

In testimony whereof I have signed my name to this specification in the presence of two subscribing

witnesses.

JOHN H. HOBBS.

Witnesses:

CHAS. H. BRADY, HOWARD HAZLETT.