



P. A. MYERS.
SAWING MACHINE.

No. 103,225.

Patented May 17, 1870.



Witnesses
Jno. V. Ellis.

Inventor
P. A. Myers,
By
J. H. Alexander
Atty.

United States Patent Office.

P. ANDREW MYERS, OF ROUND HILL, PENNSYLVANIA.

Letters Patent No. 103,225, dated May 17, 1870.

IMPROVEMENT IN SAWING-MACHINES.

The Schedule referred to in these Letters Patent and making part of the same

To all whom it may concern:

Be it known that I, P. ANDREW MYERS, of Round Hill, in the county of Adams and State of Pennsylvania, have invented certain new and useful Improvements in Sawing-Machines; and I do hereby declare that the following is a full, clear, and exact description thereof, reference being had to the accompanying drawings and to the letters of reference marked thereon, which form a part of this specification.

The nature of my invention consists in the construction and arrangement of a "sawing-machine," as will be hereinafter more fully set forth.

In order to enable others skilled in the art to which my invention appertains to make and use the same, I will now proceed to describe its construction and operation, referring to the annexed drawings, in which—

Figure 1 is a side elevation, and

Figure 2 a front view of my machine.

The frame-work of my machine is very simple, being composed of a bed, A, consisting of four beams joined together in rectangular form, from which rise four posts or standards B B.

In these posts are dovetailed, or otherwise firmly secured, two inclined beams C C, to the front ends of which are fastened two vertical bars D D.

These bars are braced by the top bars E E to the front posts B B, and under said bars D D, on the bed A, is placed a table, or rather a frame, G.

In the inclined bars or beams C C, a suitable distance in rear of the front posts B B, a shaft, H, has its bearings, which shaft is, at one end, provided with a crank, I, and at the other end with a cog-wheel, J.

This cog-wheel gears with a pinion, K, upon a crank-shaft, L, which has also its bearings in the inclined beams C C, in rear of the shaft H, and has a fly-wheel, M, attached to its end.

The crank on the shaft L is, by a pitman, N, attached or connected to the rear end of a walking-beam, O, placed upon a rocking-shaft, which has its bearings in the upper ends of the front posts B B.

The front end of the walking-beam O is, by a hook, a, connected with a cross-head, P, which moves perpendicularly up and down in grooves upon the inner sides of the vertical bars D D of the frame.

To the under side of the cross-head P, the upper end of the saw R is attached, and the lower end of the saw is attached to a cross-bar, S, through the ends of which pass rods b b, said rods being fastened in the bed A and the table or frame G, guide the saw.

Upon the frame G is placed a sliding board or carriage, T, provided with two bent bars d d, for the purpose of holding the wood on the same while it is being sawed. This carriage is slotted for a suitable distance so as to allow the saw to pass through as far as may be necessary.

The bed A may be mounted on wheels so as to be readily moved to any place desired.

Having thus fully described my invention,

What I claim as new, and desire to secure by Letters Patent, is—

The frame or table G, slotted carriage T, springs d d, rods b b, saw R, cross-head P, and walking-beam O, with its connections for receiving and imparting motion, all constructed and arranged to operate as and for the purpose set forth.

In testimony that I claim the foregoing as my own, I affix my signature in the presence of two witnesses.

P. ANDREW MYERS.

Witnesses:

DANIEL S. CHRONISTER,
O. F. NEELY.