


*S. W. Pope,*

*Plow.*


*No. 105,843.*

*Patented July 26, 1870.*

*Fig. 1.*



*Fig. 2.*



*Witnesses.*

*H. A. Pisoni*

*L. J. Noyes.*

*Inventor:*

*S. W. Pope by*

*H. W. Beadle atty*

# UNITED STATES PATENT OFFICE.

SAMUEL W. POPE, OF LOUISVILLE, KENTUCKY.

## IMPROVEMENT IN PLOWS.

Specification forming part of Letters Patent No. **105,843**, dated July 26, 1870.

*To all whom it may concern:*

Be it known that I, SAMUEL W. POPE, of Louisville, in the county of Jefferson and State of Kentucky, have invented a new and useful Improvement in Plows; and I do hereby declare that the following is a full and exact description of the same, reference being had to the accompanying drawings, and to the letters of reference marked thereon.

This invention consists in the employment of a slotted plate, in connection with a recess or notch in the end of the standard, for the purpose of securing the standard to the beam.

In the drawings, Figure 1 represents a central longitudinal section, and Fig. 2 a plan view, of my improvement in plows.

To enable others skilled in the art to which my invention appertains to make and use the same, I will now proceed to describe fully its construction and manner of operation.

A represents the beam of a plow.

B represents the plow-standard, which may be constructed in any desired form and proper manner. It is provided near its upper end with a recess or notch, *b*, cut or cast therein, the upper edge of which is slightly inclined, as shown.

C represents a metal plate, which is provided with a slot or opening, as shown, which corresponds in size with the end of the standard B. This plate is placed over the standard and rests upon the beam. When in position one of its ends, which is provided with a large bearing-surface for that purpose, is forced under the projection formed by the recess *b*, by which means the shoulder of the standard below the beam is drawn up closely to it. When the plate is forced sufficiently far beneath the projection it may be secured from accidental displacement by means of a screw, as shown. By means of this construction a simple, yet exceedingly secure fastening is obtained.

Having thus fully described my invention, what I claim as new, and desire to secure by Letters Patent, is—

The combination of the slotted adjusting-plate, notched standard, and beam, as described, for the purpose set forth.

This specification signed and witnessed this 11th day of April, 1870.

SAMUEL W. POPE.

Witnesses:

GEO. W. ANDERSON,  
JAMES A. LEECH.