




*E. Dietsch,*

*Plow.*

*No. 108,892.*

*Patented Nov. 1. 1870.*



*Witnesses.*

*Parker H. Sweet Jr.  
E. R. Brown*

*Inventor.*

*Edward Dietsch  
by J. C. Theaker  
Atty*

# UNITED STATES PATENT OFFICE.

EDWARD DIETSCH, OF FINDLAY, OHIO, ASSIGNOR TO HIMSELF AND JACOB C. POWELL, OF SAME PLACE.

## IMPROVEMENT IN PLOWS.

Specification forming part of Letters Patent No. **108,892**, dated November 1, 1870.

*To all whom it may concern:*

Be it known that I, EDWARD DIETSCH, of Findlay, in the county of Hancock and State of Ohio, have invented a new and useful Plow; and I do hereby declare that the following is a full, clear, and exact description thereof, sufficient to enable those skilled in the art to which my invention appertains to make and use the same, reference being had to the accompanying drawings, forming part of this specification, and in which—

Figure 1 is a side view of my improved plow with the wheel in place; Fig. 2, a similar view with the landside partially broken away and the wheel removed; Fig. 3, an inverted plan view of the plow without the wheel.

Similar letters of reference indicate like parts in the several figures.

My invention consists in the construction of the landside with a tongue or projection, to which the beam is attached, near the point of resistance, so as to make the draft central; also, in the peculiar construction and arrangement of a device for the vertical adjustment of the wheel to regulate the depth of the plowing, all as hereinafter more fully described.

In the drawings, A represents the landside, which is cast with a tongue or projection, *a*, on the under side. To the side of this rib is attached, by bolts or other improved means, the inner portion of the curved beam B. The attachment is thus made at or near the point of resistance, and the draft is consequently central.

To the rear part of the projection *a* is secured the right handle, *b*, of the plow, and the other is fixed to the inner face of the mold-board C. The projection *a* is slightly curved upward at its center, and at this point is placed a hanger, D, having an eye, *e*, which receives

the round center pin, *d*, rigidly attached to the flange-wheel E. The hanger D is made with two or more intersecting openings of the form shown at *e*, Fig. 2, and it is attached to the side of the tongue *a* by a bolt, *f*, having a square head adapted to fit tightly into either of the openings *e*. When the nut *g* on the inner end of the bolt *f* is loosened the hanger, and with it the wheel, may be adjusted up or down, as desired, and then fixed in position by again tightening the nut. The wheel is attached to the hanger by means of a nut screwed onto the inner end of the center pin, *d*. The dotted lines in Figs. 1 and 2 show the position of the wheel and hanger when lowered.

F represents the point, share, and vertical cutting-edge.

My arrangement of the beam serves to balance the plow and throw its entire weight on the wheel, and the latter is so constructed that the ordinary scraper is rendered unnecessary, while the lower rear point of the landside effectually clears all accumulations from the face or rim of the wheel, and requires no extra setting when the wheel is adjusted. In connection with these advantages and my improved wheel adjustment may be mentioned the simplicity and durability of construction; and all these features combine to form a light-draft, convenient, and desirable plow.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

The arrangement and combination of the tongue *a*, beam B, hanger D, and handle *b*, all as shown and described.

EDWARD DIETSCH.

Witnesses:

A. W. FREDERICK,  
JACOB F. BURKET.