

C. YENGST.

Improvement in Horse Hay Forks.

No. 116,000.

Patented June 13, 1871.

Fig. 1.




Fig. 2.





Fig. 3.



Witnesses.

Cyrus Boger
Alfred Urich

Inventor.

Cyrus Yengst.

UNITED STATES PATENT OFFICE.

CYRUS YENGST, OF ANNVILLE, PENNSYLVANIA.

IMPROVEMENT IN HORSE HAY-FORKS.

Specification forming part of Letters Patent No. 116,000, dated June 13, 1871.

I, CYRUS YENGST, of Annville, Lebanon county, State of Pennsylvania, have invented a new and Improved Hay-Fork for unloading hay by horse-power, of which the following is a specification:

My invention relates to the construction of the handle of the fork, and the arrangement of the brace-rod as connected with the handle and the spring bolt or catch; and I do hereby declare that the following is a full and exact description of the same, reference being had to the annexed drawing forming part of this specification, similar letters referring to similar parts.

Figure 1 is a sectional view of my improved fork in position for raising or lowering. Fig. 2 is a perspective view of the fork in position for unloading or discharging the hay. Fig. 3 is a detached view of the improved parts.

The nature of my invention consists in using an ordinary fork, as at B B T T T T, but with a crooked or curved handle made of wood, or wholly or in part of iron or other metal, as E C D, with a slot or opening, *a a*, in which slides the brace-rod *b b*, which is suspended from the bolt or rivet *d* running through the

lifting-rods L L. In the straight part of the handle, as at D, another slot, *i i*, is cut large enough to admit of a sliding bolt or catch, *c c*, with a spiral spring, *s*, around it, that forces the catch outward toward *e*. At *h* a cord is attached to the end of the catch to draw it inward when it is desired to unload the fork. The brace-rod *b* is kept in place with the connecting-rod *r*, which is hinged to the fork-head B at *f*, and to the brace-rod *b* at *g*.

When the fork is unloaded the handle, by its own gravity, falls down, and the end of the brace-rod *b* drops above the end of the sliding bolt *c*, as at *e*, and thus secures the fork in position for raising or lowering without danger of getting itself fast on the beams of the barn.

I claim as my invention—

The connecting-rod *r*, as attached to the beam B, and the brace-rod *b*, substantially as and for the purpose hereinbefore set forth.

CYRUS YENGST.

Witnesses:

EWD. H. WILLIAMSON,
THOS. WILLIAMSON.