



T. Cuming Jr. Plow.

No. 120,248.

Patented Oct. 24, 1871.



Witnesses:
John Becker.
Gustave Dietrich.

Inventor:
T. Cuming Jr.
PER *Wm. L.*
Attorneys.

UNITED STATES PATENT OFFICE.

THOMAS CUMING, JR., OF BROOKHAVEN, MISSISSIPPI.

IMPROVEMENT IN PLOWS.

Specification forming part of Letters Patent No. 120,248, dated October 24, 1871.

To all whom it may concern:

Be it known that I, THOMAS CUMING, Jr., of Brookhaven, in the county of Lincoln and State of Mississippi, have invented a new and useful Improvement in Plow; and I do hereby declare that the following is a full, clear, and exact description thereof, which will enable others skilled in the art to make and use the same, reference being had to the accompanying drawing forming part of this specification, in which—

Figure 1 is a perspective view of the plow inverted. Fig. 2 is a detail vertical section of the same taken through the line *x x*, Fig. 1.

Similar letters of reference indicate corresponding parts.

My invention consists in the mode of applying an adjustable share to a plow, as hereinafter fully described and subsequently pointed out in the claim.

A represents the standard, the upper end of which is attached to the plow-beam in the ordinary manner. To the lower part of the standard A is attached, or upon it is formed, the mold-board B. C is the land-side, the forward part of the upper edge of which is beveled off, and which has an upwardly-projecting flange, *c'*, formed

upon the inner side of the forward part to overlap the inner side of the lower part of the standard A, to which it is securely bolted. The lower edge of the forward part of the standard A has a long notch, *a'*, formed in it so as, in connection with the upper edge of the land-side C, to form a slot to receive the point D. The point D is made plane or flat, and has holes or slots formed in it to receive the bolts E, by which it is secured to the mold-board B, so that by loosening the nuts of the said bolts E the point D may be moved forward as it wears; or may be readily detached when worn out and replaced by a new point. The point D may be made of wrought-iron or steel, and the other parts of cast-iron or of wrought-iron, as may be desired or convenient.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

The combination, with the mold-board and land-side of a turn-plow, of share D, arranged and adjustable between them, as and for the purpose specified.

THOMAS CUMING, JR.

Witnesses:

K. R. WEBB,
A. B. R. SCHENCK.

(114)