

C. D. & R. HAZARD.

Hames.

No. 125,675.

Patented April 16, 1872.

Fig. 1.




Fig. 2.




Fig. 3.





Fig. 4.



Witnesses.

J. H. Burridge.
M. R. Butler

Inventor.

C. D. & R. Hazard.
per Burridge & Co.
Atty

UNITED STATES PATENT OFFICE.

CLARK D. HAZARD AND RUSEL HAZARD, OF CLEVELAND, OHIO.

IMPROVEMENT IN HAMES.

Specification forming part of Letters Patent No. 125,675, dated April 16, 1872.

To all whom it may concern:

Be it known that we, C. D. HAZARD and RUSEL HAZARD, of Cleveland, in the county of Cuyahoga and State of Ohio, have invented a certain new and Improved Hame; and we do hereby declare that the following is a full, clear, and complete description thereof, reference being had to the accompanying drawing making part of the same.

SPECIFICATION.

Figures 1, 2, and 3 are side views of the upper end of the hame, having attached thereto the improvement. Fig. 4 is a detached section.

Like letters of reference refer to like parts in the several views.

This invention has for its object the fastening together of the upper ends of the hames in such way that said fastening may be so adjusted as to adapt the hames to the neck of the horse or horses, and to fit the collar more snugly in connection with which it may be used. Of said invention the following is a more full and complete description, and is an improvement of an invention for which a patent was granted to me September 10, 1861.

In the drawing, Fig. 1, A represents the wood part of the hame, which is or may be of the ordinary shape. B is an iron band covering the end for its strength and protection. The inside part of the band is perforated with a series of holes, C, the purpose of which will presently be shown. D is a ring loosely fitted to the hame, so that it will slide thereon the length of the series of holes. E is a block, a detached view of which is shown in Fig. 4, in which figure it will be seen that one side thereof is hollowed out, so that the ring D referred to will fit therein, as shown in Fig. 1; and that on the opposite side is a nib, F, of a size to fit

the holes C, and in which it is lodged when in connection with the hame, as shown in Fig. 1.

The practical use of the above-described device is as follows: The strap G, whereby the two parts of the hame are connected, is passed through the ring D. Between the strap and the hame is inserted the block E, in such relation to the hame and strap that said strap is held in the hollow of the block and the nib is received into one of the holes, as shown in Fig. 1. By this device the ring cannot slip on the hame, as the nib of the block holds it in place, and the thickness of the strap prevents the nib from coming out of the hole; hence the strap is securely held in its attachment with the hame.

The advantage of this device is that the strap crosses from hame to hame flatwise, and will therefore lie more closely upon the horse's collar than if it passed across edgewise, as in the old way; and it looks much neater than that shown in my patent, for in that manner of fastening the holes for the admission of the nib (which is on a ring, and not on a block) are on the outside of the hame, and therefore in sight, which mars the appearance of the hame; but in this, my present invention, the plain side of the band is on the outside, making the hame look much neater and of a better finish.

Claim.

What we claim as our invention, and desire to secure by Letters Patent, is—

The ring D, block E, and nib F, in combination with the hame A and strap G, substantially as and for the purpose specified.

CLARK D. HAZARD.

Witnesses: RUSEL HAZARD.

J. H. BURRIDGE,

C. M. TRIVER.