

J. M. BEEBE.
Fence Posts.

No. 136,406.

Patented March 4, 1873.

Fig. 1.




Fig. 2.





Fig. 3.



Edward Wilhelm
Jno J. Bonner
Witnesses

James M. Beebe Inventor
by Jay Hyatt
Att'y

UNITED STATES PATENT OFFICE

JAMES M. BEEBE, OF CASSADAGA, NEW YORK, ASSIGNOR TO HIMSELF AND
CHARLES V. BEEBE, OF SAME PLACE.

IMPROVEMENT IN FENCE-POSTS.

Specification forming part of Letters Patent No. **136,406**, dated March 4, 1873.

To all whom it may concern:

Be it known that I, JAMES M. BEEBE, of Cassadaga, in the county of Chautauqua and State of New York, have invented a certain new Improvement in Fence-Posts, of which the following is a specification:

My improvement relates to that class of fence-posts in which the lower part which enters the ground is made of iron and the upper portion of wood. The invention consists of a metallic base part inserted in a slot in the wooden portion of the post, and provided with two vertical flanges, the upper portions of which overlap the lower end of the post on opposite sides, and secure the base part in the slot of the wooden post without requiring any additional fastening device, said flanges serving at the same time to give the required stiffness to the base part.

In the accompanying drawing, Figure 1 is an elevation of my improved fence-post arranged in a board-fence. Fig. 2 is a perspective view of the fence-post; and Fig. 3, a cross-section on an enlarged scale in line *xx*, Fig. 1.

Like letters designate like parts in all of the figures.

A represents the wooden portion of the post, and *a* the slot formed in the lower end thereof. B is the web or main portion of the metallic base part, which is preferably constructed of sheet-iron, and *b b* the vertical flanges thereof, arranged at right angles to the web B, and turned in opposite directions, as clearly shown in Figs. 2 and 3. The web B of the base-piece

is inserted in the slot *a* of the post A, when the upper portions of the flanges *b b* overlap and fit snugly against the front and back of the wooden post, whereby a firm connection of the base-piece with the latter is obtained without the employment of any additional fastening device. The flanges *b b* serve at the same time to give the required stiffness to the base-piece, and oppose the necessary resistance to any movement in the direction of the web B. The base-piece being constructed of thin metal, it is readily driven into the ground, and requires only a narrow slot in the post A for its connection therewith, which does not materially reduce the strength of the post. The upper corners *b'* of the flanges *b* may be indented in the post A, so as to hold it more firmly against vertical displacement.

My improved fence-post is of the simplest construction, and very cheaply produced, while it possesses the required strength and stability.

I claim as my invention—

A fence-post composed of the wooden portion A, provided with the slot *a* and the metallic base-piece B inserted therein, and provided with the fastening-flanges *b b*, resting against the front and back of the wooden post, substantially as shown and described.

JAMES M. BEEBE.

Witnesses:

W. W. FISHER,
A. BAILEY.