


R. S. BABBITT.

Forepart Irons for Shoemakers.

No. 146,978.

Patented Feb. 3, 1874.



WITNESSES.

John H. Lawlor
Frederick A. Hering.

INVENTOR.

Reuben S. Babbitt
By Gidley & Warner
Atty

UNITED STATES PATENT OFFICE.

REUBEN S. BABBITT, OF JACKSON, MICHIGAN, ASSIGNOR TO AUSTIN
WISWALL, OF CHICAGO, ILLINOIS.

IMPROVEMENT IN FORE-PART IRONS FOR SHOEMAKERS.

Specification forming part of Letters Patent No. **146,978**, dated February 3, 1874; application filed
July 17, 1873.

To all whom it may concern:

Be it known that I, REUBEN S. BABBITT, of Jackson, in the county of Jackson and State of Michigan, have invented certain new and useful Improvements in Fore-Part Irons for Shoemakers, of which improvement the following is a full, clear, and exact description, which will enable others skilled in the art to which my invention appertains to make and use the same, reference being had to the accompanying drawing forming a part of this specification, and in which—

Figures 1 and 2 represent side elevations of a fore-part iron provided with my improvements, and Fig. 3 a vertical central section in the plane of the line *x x*.

Like letters of reference indicate like parts.

The object of my invention is to improve the construction and operation of fore-part irons, and to avoid the use of numerous tools in doing the work usually done by this class of devices; and to that end my invention consists of an adjustable gage, arranged upon a screw-pin extending from the end of the handle, in combination with a laterally-adjustable stock, provided with one or more lips, and arranged in the gage, and extending between it and the handle, substantially as hereinafter specified. It also consists of a removable and adjustable lip, attached to the stock in a manner substantially the same as hereinafter described.

In the drawing, A represents the handle of the tool. B is a screw-pin extending from the end of the handle, and rigidly attached thereto. C is a gage upon the outer or screw-threaded end of the pin B. The gage is slotted from side to side, as represented in Fig. 3. The body of the stock is arranged in the slot of the gage, and is capable of being moved freely therein. The stock is also so constructed as to extend between the handle and the gage, as shown; and the part thus extended may be slotted to receive the pin B and admit of a considerable lateral movement of the stock, as shown in Fig. 3. E is a rigid lip on the stock. F is an adjustable lip, attached to the stock. In order to render the lip F adjustable on the stock,

I cut a longitudinal slot, *a*, in the lip, and attach the latter to the stock by means of a screw, *a'*, arranged in the slot *a*. In order to prevent the lip F from being tilted from its position while the tool is being used, I notch the lower end of the said lip, as shown at *e*, and extend a pin, *e'*, from the stock into the said notch.

It will be perceived, from the foregoing description, that the gage is adjustable with reference to the handle, and that the lips E and F are adjustable laterally with reference to the gage, and according to the thickness of the sole of the boot or shoe, it being understood that the handle is turned for this purpose until it is drawn away from the stock. When the stock is adjusted, the handle is turned in the reverse direction until the stock is forced against the gage with sufficient firmness to be prevented from being moved laterally while the tool is being used.

It will also be observed that the lip F is removable, and may be readily made either flush with the face of the stock, or extended a greater or less distance from it.

The gage may be rabbeted to receive the stock, instead of being slotted for that purpose.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

1. The adjustable gage arranged upon a screw-pin extending from the end of the handle, in combination with a laterally-adjustable stock, provided with one or more creasing or marking lips, and arranged in the gage, and extending between it and the handle, substantially as and for the purposes specified.

2. The removable and adjustable lip F, attached to the laterally-adjustable stock, substantially as specified, in combination with the adjustable gage, arranged upon a screw-pin extending from the end of the handle, substantially as and for the purpose specified.

REUBEN S. BABBITT.

Witnesses:

L. M. POWELL,
A. WISWALL.