


W. W. KOLLOCK.  
Shot-Pouch Slings.

No. 156,930.

Patented Nov. 17, 1874.



WITNESSES:

*Francis Mc Ardle,*  
*Stidquick*

INVENTOR:

*W. W. Kollock*  
BY *Munn & Co.*  
ATTORNEYS.

# UNITED STATES PATENT OFFICE.

WILLIAM W. KOLLOCK, OF AUGUSTA, GEORGIA.

## IMPROVEMENT IN SHOT-POUCH SLINGS.

Specification forming part of Letters Patent No. **156,930**, dated November 17, 1874; application filed July 18, 1874.

*To all whom it may concern:*

Be it known that I, WILLIAM W. KOLLOCK, of Augusta, in the county of Richmond and State of Georgia, have invented a new and useful Improvement in Pouch-Sling, of which the following is a specification:

The figure is a perspective view of my improved sling.

My invention has for its object to furnish a simple and convenient device for carrying a shot pouch, which shall be so constructed as to carry the pouch securely and prevent it from being lost by the pulling off of the rings, as frequently happens when the pouches are carried in the ordinary way.

The invention consists in an improved pouch-sling formed of straps arranged in connection with each other, as hereinafter fully described.

A is the shoulder-strap, which is made in two parts connected by a buckle, so that the said strap can be conveniently lengthened and shortened, as may be required. To the ends of the shoulder-strap A is attached a ring-strap, B, of such a size as to fit around the smaller part of the pouch, as indicated in dotted lines in the figure. To the strap A, at a little distance from its ends, is attached a second ring-strap, C, made larger than the ring-strap B,

so as to fit around the larger part of the pouch, as indicated in dotted lines in the figure. D is a short strap secured to the ring-straps B C midway between the end parts of the shoulder-strap A, and to its end, at or near the edge of the larger ring-strap, C, is attached a buckle. To the opposite sides of the ring-straps B C, and also midway between the end parts of the strap A, is attached a strap, E, the free end of which is designed to be passed through the ring of the pouch and buckled into the buckle of the strap D.

With a sling thus constructed the pouch can be easily and conveniently carried, and cannot become detached and lost, and, at the same time, will always be in a convenient position for use in loading the gun.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

An improved pouch-sling formed of the straps A B C D E, arranged in connection with each other, substantially as herein shown and described.

WILLIAM W. KOLLOCK.

Witnesses:

EDWARD M. HABERSHAM,  
FRANCIS L. NEUFVILLE.