

E. A. PERRY, Jr. & G. M. DWIGHT.

Head-Blocks.

No. 161,897.

Patented April 13, 1875.

Fig. 1.




Fig. 3.





Fig. 2.



Witnesses

D. R. Cowell
Alonzo Hughes

Inventors.

Ezra A. Perry Jr.
George M. Dwight Jr.
By their Atty. J. H. Reigart

UNITED STATES PATENT OFFICE.

EZRA A. PERRY, JR., AND GEORGE M. DWIGHT, OF OREGON, ILLINOIS.

IMPROVEMENT IN HEAD-BLOCKS.

Specification forming part of Letters Patent No. **161,897**, dated April 13, 1875; application filed September 26, 1874.

To all whom it may concern:

Be it known that we, EZRA A. PERRY, Jr., and GEORGE M. DWIGHT, of Oregon, Ogle county, State of Illinois, have invented new and useful Improvements in Buggies or Carriages; and we do hereby declare the following to be an exact description thereof, reference being had to the accompanying drawings and to the letters of reference marked thereon, making a part of this specification, in which—

Figure 1 represents the axle, tongue, fifth-wheel, or circular bearings of the metallic head-block, the brace and the metallic head-block in two pieces, divided angularly at the center. Fig. 2 represents the center part of the head-block, with its center groove half surrounding the standard. Fig. 3 represents the angular movable part of the head-block, showing the other half of the groove, in which the standard fits and works. Fig. 4 represents the brace that secures the tongue with the lower part of the axle, where it is fastened by a set-screw.

The nature of my invention consists in the metallic head-block in two pieces, with a groove in the center to fit closely around the standard.

A A represent the metallic head-block at the top of the front axle H of a carriage or buggy, having an angular piece, A, at the center, fitting against the rear side or back of the head-block, thus forming two pieces, A A, connected by screw-bolts B B, and having a

T-shaped groove, J, in the center, corresponding with the form of the T-shaped standard D, in which the standard D works closely, yet easily and regularly, with the direction of the axle H. The T-shaped standard D is permanently fastened into the axle H, and has a collar, K, at its center, for the head-block A to rest and turn upon, the standard being in lieu of a coupling bolt or pin, for greater security, as the ordinary loose coupling-pins frequently wear and drop out—the cause of numerous accidents. The brace G connects the lower part of the tongue L with the lower part of the axle H. It is fastened to tongue L by two screws, and supports the fifth-wheel or bearings M, and is attached to the lower part of the axle by a set-screw, E, to hold the brace.

What we claim as our invention, and desire to secure by Letters Patent, is—

1. The metallic head-block made in two pieces, A A, held together by screws B B, having a recess, C, for the spring-bolt to rest in, and having in the center a groove, J, in combination with the standard D, as and for the purposes set forth.

2. The T-shaped standard D, fitted to and working in the corresponding groove J in the head-block A, and in combination therewith, as set forth.

EZRA A. PERRY, JR.

Witnesses: GEORGE M. DWIGHT.
JAMES H. CARTWRIGHT,
W. H. GUILFORD.