


W. W. FOWLER.
Drinking-Cup for Invalids.

No. 162,640.

Patented April 27, 1875.



Witnesses.
J. W. Shumway.
Oliver Broughton.

Wm. W. Fowler
Inventor
By Atty.
John S. Earle

UNITED STATES PATENT OFFICE.

WILLIAM W. FOWLER, OF GUILFORD, CONNECTICUT.

IMPROVEMENT IN DRINKING-CUPS FOR INVALIDS.

Specification forming part of Letters Patent No. **162,640**, dated April 27, 1875; application filed March 27, 1875.

To all whom it may concern:

Be it known that I, WILLIAM W. FOWLER, of Guilford, in the county of New Haven and State of Connecticut, have invented a new Drinking-Cup for Invalids; and I do hereby declare the following, when taken in connection with the accompanying drawings and the letters of reference marked thereon, to be a full, clear, and exact description of the same, and which said drawings constitute part of this specification, and represent, in—

Figure 1, vertical central section.

This invention relates to the construction of a goblet, so as to enable invalids and others to drink therefrom while in a recumbent position; and the invention consists in a goblet with a tubular stem, closed by a valve at the bottom of the bowl, operated by a spindle from beneath, and combined with a transverse tube to conduct the contents of the goblet, when the valve is open, to the mouth of the person, as more fully hereinafter described.

A is the bowl of the goblet, resting upon a stem, B, on a base, C, in substantially the usual manner for goblets. The stem B is made tubular, or with a passage extending from the base into the bowl—the bowl constructed with a seat, into which the valve D closely fits, so as to close the opening at the bottom of the goblet. From this valve a spindle, *a*, extends down through the base, and terminates in a head, E. A packing, *b*, is applied around the

spindle, and between the said packing and the head E a spring, *d*, is arranged, the tendency of which is to hold the valve in a closed position. By pressing up upon the head E, the valve D is raised, as denoted in broken lines, thus opening the passage from the bowl into the stem. At a convenient point in the stem a tube, F, is attached, leading beyond the base, and should be turned downward. This tube opens into the passage in the stem; hence, when the valve is opened the contents of the bowl will flow out through the tube F without tilting the goblet. The tube F should be made so as to screw into the stem, and thereby be detachable, so that, when not required for its specially-intended use, it may be used as a common goblet.

The person desiring the contents of the goblet has the outer end of the tube F placed in his mouth; then the valve opened to allow the contents to pass from the bowl to the mouth.

I claim—

The herein-described drinking-cup, consisting of the bowl A, the tubular stem B upon the base C, the valve D to close the passage from the bowl to the stem, the head E, the spring *d*, and the transverse tube F, substantially as described.

WM. W. FOWLER.

Witnesses:

JOHN E. EARLE,

CLARA BROUGHTON.