
## R. C. HAYTON & C. A. HURLBURT. Saw-Buck.

No. 164,556.

Patented June 15, 1875.



WITN ESSES.

P. C. Dieterich

Mh. Manth

R. C. Flayton

& d. Hurlbrit

For

\$ 14 Alexander

THE GRAPHIC CO.PHOTO-LITH. 39 & 41 PARK PLACE, N.Y.

## United States Patent Office

ROB. C. HAYTON AND CHARLES A. HURLBURT, OF YPSILANTI, MICHIGAN.

## IMPROVEMENT IN SAW-BUCKS.

Specification forming part of Letters Patent No. 164,556, dated June 15, 1875; application filed March 30, 1875.

To all whom it may concern:

Be it known that we, R. C. HAYTON and C. A. HURLBURT, of Ypsilanti, in the county of Washtenaw and State of Michigan, have invented certain new and useful Improvements in Saw-Bucks; and we do hereby declare that the following is a full, clear, and exact description thereof, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form part of this specification.

The nature of our invention consists in the construction and arrangement of a saw-buck, as will be hereinafter more fully set forth.

In order to enable others skilled in the art to which our invention appertains to make and use the same, we will now proceed to describe its construction and operation, referring to the annexed drawing, which represents a cross-section of our saw-buck.

Each side of our saw-buck is composed of an ordinary iron cross, A, such as are used for connecting gas-pipe, to make the rest for the stick of wood upon the saw-buck. This cross consists of a piece of iron, hollow at all the four ends, with or without interior

screw-threads. Into each of these ends is screwed or driven an arm, B, to complete the side of the saw-buck. The arms B B may be made of wood or metal, and if made of metal we prefer to make them of hollow tubing, as shown in the drawing. On the arms, which form the legs of the saw-buck, are placed ordinary T-joints C, for the attachment of the foot-brace D. These T-joints and foot-brace need only be used on one side of the saw-buck. On the other side a rod or brace, E, may be simply screwed into the legs, if so desired.

Having thus fully described our invention, what we claim as new, and desire to secure by

Letters Patent, is—

The combination of the cross A, arms B, T-joints C, and foot-brace D, all substantially as and for the purposes herein set forth.

In testimony that we claim the foregoing as our own we affix our signatures in presence of two witnesses.

> ROB. C. HAYTON. CHARLES A. HURLBURT.

Witnesses:

S. M. CUTCHEON, FRED. A. HUNT.