

W. M. THOMPSON.
Dumping-Wagon.

No. 169,060.

Patented Oct. 19, 1875.






Fig. 2



WITNESSES
Wm. A. Skinkle.
C. L. Ewert

By

INVENTOR
W. M. Thompson
Alexander Mason
Attorney

UNITED STATES PATENT OFFICE.

WILLIAM M. THOMPSON, OF CARLISLE, PENNSYLVANIA.

IMPROVEMENT IN DUMPING-WAGONS.

Specification forming part of Letters Patent No. 169,060, dated October 19, 1875; application filed September 2, 1875.

To all whom it may concern :

Be it known that I, WILLIAM M. THOMPSON, of Carlisle, in the county of Cumberland and in the State of Pennsylvania, have invented certain new and useful Improvements in Cart-Chutes; and do hereby declare that the following is a full, clear, and exact description thereof, reference being had to the accompanying drawings, and to the letters of reference marked thereon, making a part of this specification.

My present invention is intended as an improvement upon the coal-wagon for which Letters Patent No. 165,632 were granted to me July 13, 1875; and it consists, particularly, in the construction of the sectional folding chute, as will be hereinafter more fully set forth.

In order to enable others skilled in the art to which my invention appertains to make and use the same, I will now proceed to describe its construction and operation, referring to the annexed drawing, in which—

Figure 1 is a rear elevation of a coal-cart embodying my invention. Fig. 2 is a longitudinal vertical section of the same. Figs. 3 and 4 are detached views, showing the sliding joint in the chute. Figs. 5 and 6 are detached views, showing the folding joints thereof.

A represents the coal-cart constructed substantially as described in my former patent, above referred to, and provided with end gates B B, which are hinged to swing upward. At the rear end of the cart is a stationary spout, C, provided under its outer end with a fender, *a*, for supporting the chute, which is made in four sections, D¹, D², D³, and D⁴. The first or upper section D¹ slides within the second section D², it being connected thereto by flanged pieces *b b*, which are attached to one section, and fit over the edge of the other section, and thus, also, form stops to prevent these two sections from being pulled apart. On the under side of the first section D¹, at the inner end, are two inclined or curved feet, *d d*, which, when said section is drawn out from under the spout C, ride upon the fender or bail *a*, and lift said section up close against the under side of the spout, the feet also form-

ing stops against said bail or fender to prevent the section D¹ from coming out from under the spout. The section D³ is connected to the section D² by means of L-shaped hinges E, constructed in such a manner that one leaf of each hinge will enter and pass in between the two parts of the other leaf, thereby making the hinge very strong, and the two leaves of the hinge are so arranged that, when the sections of the chute are extended, the upper edge of the lower section D³ will be immediately under the lower edge of the section D². The section D⁴ is hinged to the section D³ in the same manner, and by the same means.

The various sections of the chute, as well as the spout C, are made in the form shown in Figs. 3 and 5—that is, inclined from each side toward the center, and with flanges projecting upward along each side, the whole made in one piece.

When the chute is not in use the upper sections D¹ D² are closed up together, and then moved inward under the spout and body of the cart. The lower sections D³ D⁴ are folded under, into each other, and supported by the fender or bail *a*, as represented by dotted lines in Fig. 2.

By the construction of the chute the coal falls toward the center, and goes out freely without any liability of its clogging.

Having thus fully described my invention, what I claim as new, and desire to secure by Letters Patent, is—

The combination of the spout C, with bail *a*, sliding-chute sections D¹ D², the section D¹ having curved feet *d*, and the flanged pieces *b b* on the sections D¹ D², and the hinged sections D³ D⁴, with hinges E E, all constructed substantially as and for the purposes herein set forth.

In testimony that I claim the foregoing I have hereunto set my hand this 27th day of August, 1875.

W. M. THOMPSON.

Witnesses:

J. M. MASON,
C. L. EVERT.