

G. W. MCGILL.
SUSPENSION RING.

No. 172,466.

Patented Jan. 18, 1876.

Fig. 1.




Fig. 2.




Fig. 3.





Fig. 4.



WITNESSES:

James Johnson
M. L. McGill

INVENTOR:

George W. McGill

UNITED STATES PATENT OFFICE.

GEORGE W. MCGILL, OF NEW YORK, N. Y.

IMPROVEMENT IN SUSPENSION-RINGS.

Specification forming part of Letters Patent No. 172,466, dated January 18, 1876; application filed April 22, 1875.

To all whom it may concern:

Be it known that I, GEORGE W. MCGILL, of the city, county, and State of New York, have invented a new and useful Suspending Device for Hanging or Suspending Show-Cards, Pictures, &c.; and I do hereby declare the following to be a full and exact description thereof, reference being had to the accompanying drawing making part of this specification, and to the figures and letters of reference marked thereon, in which—

Figure 1 shows a front view of the device; Fig. 2, a back view of the same, attached to a card. Fig. 3, a sectional view of the device, taken on the line *xx* of the Fig. 2, and Fig. 4 a detail view.

My invention consists in a piece of suitable sheet metal, having its body-portion struck up or fashioned into any ornamental design or form, as shown at A, in the figures. From the top of the body A rises the suspending-loop B. The plate *b*, forming the center of the loop B, is disconnected from the sides and top of the loop, but is left connected with the top of the body A at the point *b'*. From the bottom of the body A extends a pointed spur, C. Both the plate *b* and spur C are

bent out on lines parallel with themselves, and at right angles from the body A. The device is applied by forcing the spur C through the card to be suspended, and turning it up and then turning the plate *b* down over the top of the card and over the turned-up point of the spur C, as shown in Figs. 2 and 3.

In the drawing, D represents the card. The plate *b* guides the point of puncture of the spur C, and covers its point, when inserted in the card to be suspended.

The spur C may be cut from the center of the body A, as shown in Fig. 4, but I prefer extending it from the bottom, as shown in the other figures, as making a better article.

What I claim as my invention, and desire to secure by Letters Patent, is—

My within-described suspending device consisting of the body A, loop B, plate *b*, and spur C, cut and swaged from a single piece of sheet metal, as herein shown, to operate in the manner and for the purposes herein specified.

GEORGE W. MCGILL.

Witnesses:

S. CHASE,

CHARLES TAPPEN.