
G. V. SHEFFIELD.

METHOD OF UNITING PIECES OF LEATHER, &c.

No. 173,868.

Patented Feb. 22, 1876.



John Soethals Alex F. Roberts

BY Municipal ATTORNEYS.

UNITED STATES PATENT OFFICE

GEORGE V. SHEFFIELD, OF EAST NEW YORK, N. Y.

IMPROVEMENT IN THE METHODS OF UNITING PIECES OF LEATHER, &c.

Specification forming part of Letters Patent No. 173,868, dated February 22, 1876; application filed January 15, 1876.

To all whom it may concern:

Be it known that I, GEORGE V. SHEFFIELD, of East New York, Kings county, New York, have invented a new and Improved Method of Uniting Pieces of Leather, &c., of which

the following is a specification:

My invention consists of a new method of uniting pieces of leather, cloth, &c., by looping an under thread through a loop of the needle-thread and drawing the under-thread loop up to the surface by the needle-thread, thus quadrupling the lower thread in the work, and binding the same by the upper thread, and connecting these quadrupled threads from hole to hole by a thread on each side of the work.

The method is mainly designed for uniting boot and shoe soles with a waxed thread, which, by so doubling in the work and securing by the wax, makes a fastening of superior

strength.

The drawing is a section of two pieces of leather sewed together by my improved stitch, showing also the needle for the upper and pusher for the lower thread.

A and B are the two pieces of leather sewed

to be inserted in the ordinary way, making a loop, D, on the under side, in which the under thread E is looped, as shown at F, by pusher J, or by an awl-hook or other contrivance, which draws out and leaves the loop, after which the loop of the upper thread is drawn back flush with the upper surface of the work, thus again doubling loop F, and at the same time drawing it up taut and locking it on the upper side.

Having thus described my invention, I claim as new and desire to secure by Letters Pat-

ent--

The method of uniting two pieces of leather herein described, which consists in passing the loop F of an under thread, E, through the loop D of an upper thread, C', first brought down through both pieces, the loop of upper thread being then drawn back flush with the upper surface of work, as shown and described.

GEORGE V. SHEFFIELD.

Witnesses:

T. B. Mosher,
ALEX. F. Roberts.