




PLOW.

Patented May 16, 1876.



A. W. Mungqvist
John Goethals

D. H. Garrard
BY *Mumford*
ATTORNEYS.

ATTORNEYS.

UNITED STATES PATENT OFFICE.

DAVID H. JARRARD, OF TALLADEGA, ALABAMA.

IMPROVEMENT IN PLOWS.

Specification forming part of Letters Patent No. **177,520**, dated May 16, 1876; application filed March 21, 1876.

To all whom it may concern:

Be it known that I, DAVID H. JARRARD, of Talladega, in the county of Talladega and State of Alabama, have invented a new and useful Improvement in Plows, of which the following is a specification:

Figure 1 is a side view of a part of my improved plow. Fig. 2 is a detail section of the same, taken through the line *x x x x x*, Fig. 1. Fig. 3 is a detail cross-section of the same, taken through the line *y y*, Fig. 1. Fig. 4 is a detail cross-section of the same, taken through the line *z z*, Fig. 1.

Similar letters of reference indicate corresponding parts.

The object of this invention is to furnish an improved plow which shall be so constructed that the plow-standard may be adjusted to give any desired pitch to the plow, and may be held securely in place when adjusted, and which will support the wing of the plow-plate to prevent it from being bent or broken.

The invention will first be described in connection with the drawing, and then pointed out in the claim.

A represents a plow-beam, in a mortise in which is secured a bar, B. To the opposite sides of the lower end of the bar B are pivoted the upper ends of two slightly-curved parallel bars, C, the lower ends of which are formed solid with each other. Between the middle parts of the bars C is pivoted the end of the bent or elbow bar D, the upper end of which is bent outward to lie upon the under side of

the beam A, and is slotted to receive the bolt E, by which it is secured to said beam, so that by loosening the said bolt E the standard C may be adjusted at any desired pitch. The stay or brace D may be placed in the rear of the standard C, as shown in Fig. 1, or in front of said standard, as indicated by the bolt-hole *a'*.

When the brace D is placed in front of the standard C, there may be pivoted to its angle a rotary cutter, F, to cut stubble, sod, &c., above the plow. G is the plow-plate, which is secured to the lower part of the standard C by a bolt, *g'*, passing through it, and through the space between the bars of the standard. H is an angle-plate, which is secured to the side of the lower part of the standard C by two bolts, *h'*, passing through a slot in one of the bars of the standard C. The plate H is designed to support the wing of the plow-plate when made wide, to prevent it from being bent or broken.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

The combination of crooked brace D, made reversible before and behind the standard, with the sod-cutter F, secured detachably, as and for the purpose specified.

DAVID H. JARRARD.

Witnesses:

H. H. HAMILL,
I. H. VANDINE.