

J. S. HEACOCK.

FASTENERS FOR THE MEETING-RAILS OF SASHES.

No. 180.877.

Patented Aug. 8, 1876.

Fig. 1.





Fig. 2.



J. S. Heacock
John Otto, Jr. } Witnesses

J. S. Heacock Inventor

UNITED STATES PATENT OFFICE.

J. STONE HEACOCK, OF BUFFALO, NEW YORK.

IMPROVEMENT IN FASTENERS FOR THE MEETING-RAILS OF SASHES.

Specification forming part of Letters Patent No. **180,877**, dated August 8, 1876; application filed February 3, 1875.

To all whom it may concern:

Be it known that I, J. STONE HEACOCK, of Buffalo, in the county of Erie and State of New York, have invented an Improvement in Window-Fasteners, of which the following is a specification:

The primary object of my invention is to prevent burglars from moving the levers of window-fasteners by operating from without with thin instruments thrust between the sash.

My invention consists of a spring secured directly to the rail of the sash, and provided with a rectangular notch, into which the lever-arm automatically locks itself, as will be hereinafter more fully set forth and definitely claimed.

Figure 1 is a plan view embodying my invention. Fig. 2 is a side view of the same.

A is a piece of spring metal, or some other suitable substance, of sufficient length, breadth, and thickness to hold the lever securely against turning, in form resembling the handle of a spoon, having a notch, *a*, near the middle of the curve of width and depth sufficient to receive and hold immovable the

end of the lever. C, B, and D are the fixed parts of an ordinary window-fastener. The spring for locking the lever C in the proper radial position is independent and separate from the segmental guide D, which, with the lever C, serves to draw the meeting-rails together. The spring A is also so shaped that the end of the lever may ride up to and into the slot *a*. It will also be observed that the spring A may be applied to and used with the ordinary fasteners now in use without any modification of said fasteners.

Having thus fully described my invention, what I claim as new, and desire to secure by Letters Patent, is—

A single spring, secured directly to the rail of the sash, and provided with a rectangular slot, into which the lever-arm automatically locks itself against movement in either direction, substantially as described and shown, for the purpose set forth.

J. STONE HEACOCK.

Witnesses:

A. S. ALLIS,
L. C. TIBBITTS.