



J. PENTREATH.  
ADJUSTABLE PLOW-BEAM.

No. 181,471.

Patented Aug. 22, 1876.



WITNESSES  
Frank L. Curand  
Henry N. Miller

INVENTOR  
John Pentreath  
By T. H. Alexander  
Attorneys.

# UNITED STATES PATENT OFFICE.

JOHN PENTREATH, OF NEWARK, NEW JERSEY, ASSIGNOR TO THE NEW YORK PLOW COMPANY, OF NEW YORK, N. Y.

## IMPROVEMENT IN ADJUSTABLE PLOW-BEAMS.

Specification forming part of Letters Patent No. 181,471, dated August 22, 1876; application filed May 18, 1876.

*To all whom it may concern:*

Be it known that I, JOHN PENTREATH, of Newark, in the county of Essex and State of New Jersey, have invented certain new and useful Improvements in Method of Adjusting and Fastening Movable Beams of Plows; and I do hereby declare that the following is a full, clear, and exact description thereof, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form part of this specification.

My invention relates to adjustable plow-beams; and it consists in the devices for holding the beam at any angle desired, as will be hereinafter more fully set forth.

In the annexed drawing, Figure 1 is a longitudinal section of my invention. Fig. 2 is a plan view of the same.

A represents the upper portion of a plow foot or standard to which the handles B B are secured, said handles being connected by a metal cross-bar, C. D is the plow-beam pivoted and fastened by means of a bolt, *a*, passing through the beam, and into the standard, and screwing through a nut, *b*, placed in a mortise in the standard. Through the rear end of the beam D is passed a bolt, *d*, the lower end of which forms a hook or loop, *e*, and passes under the cross-bar C, the end of the hook or loop entering a hole in the under

side of the beam. On the upper end of the bolt *d* is screwed a nut, *h*, which tightens the loop around the bar C, and holds the beam firmly thereon. To prevent slipping, the upper surface of said bar is corrugated, toothed, or otherwise made rough, as shown. By this means the beam can easily and quickly be adjusted to any angle desired, and held firmly in any required position.

I do not, broadly, claim a plow-beam pivoted to the standard, and held at any desired angle, as I am aware that such is not new.

Having thus fully described my invention, what I claim as new, and desire to secure by Letters Patent, is—

The combination, in a plow, of the beam D, pivoted by a bolt, *a*, to the standard A, the cross-bar C connecting the two handles and serrated upon its upper face, and the J-shaped screw-bolt *d* and nut *h*, whereby the plow-beam may be moved and adjusted at any desired inclination, substantially as herein set forth.

In testimony that I claim the foregoing as my own invention I affix my signature in presence of two witnesses.

JOHN PENTREATH.

Witnesses:

JOHN Q. CROSBY,  
E. A. VAN WYCK.