





F. RAUH.
PLANING TOOL.

No. 181,594.

Patented Aug. 29, 1876.



Witnesses

Wesley Johnston
B. Le. Johnston

Inventor

Frederick Rauch
By A. C. Johnston
His Attorney

UNITED STATES PATENT OFFICE.

FREDERICK RAUH, OF PITTSBURG, PENNSYLVANIA.

IMPROVEMENT IN PLANING-TOOLS.

Specification forming part of Letters Patent No. **181,594**, dated August 29, 1876; application filed June 19, 1876.

To all whom it may concern:

Be it known that I, FREDERICK RAUH, of Pittsburg, in the county of Allegheny and State of Pennsylvania, have invented Improvement in Planing-Tools; and I do hereby declare that the following is a full and exact description thereof, reference being had to the accompanying drawings, and to the letters of reference marked thereon.

My invention relates to an improvement in planing-tools for planing cylindrical articles of wood; and consists of three jaws, pivoted together, and furnished with adjusting-screws, adjustable cutter, and handle, combined, arranged, and operating with relation to each other, as hereinafter described.

To enable others skilled in the art to make and use my invention, I will proceed to describe its construction and operation.

In the drawings, Figure 1 is a side view of my improvement. Fig. 2 is a front view. Fig. 3 is a vertical section. Fig. 4 is a broken section, showing the interior of the pivoted jaws.

The jaws A and B are pivoted at C, and are provided with a handle, *l*. The jaw D is pivoted to the jaw A at *e*, the end *f* of which passes through an aperture in the jaw A, as shown in Figs. 2, 3, 4. The jaws are adjusted through the medium of screws *i* and *j*, the screw *i* adjusting the jaw D, and the screw *j* adjusting the jaw A with relation to the jaw

B, the jaw D being used with relation to the jaw B, for the purpose of planing articles of small diameter, the jaws A and B being used for planing articles of larger diameter. The jaws A and B are furnished with screw-threads, as indicated at *m* in Fig. 4. The end *f* of the jaw D is also furnished with screw-threads, as indicated at *m'* in Fig. 4. The jaw B is furnished with an adjustable plane-bit, *g*, held in position by means of the set-screw *h*.

The operation of my improvement is as follows: The jaws are adjusted with relation to the diameter of the cylindrical article to be planed, so that the screw-threads of the jaws will impinge upon it, and, by revolving the tool around the article, the bit *g* will plane or cut off the surface in proportion to the cut given to it, the screw *m* gradually leading the tool along the cylindrical article.

Having thus described my improvement, what I claim is—

The combination of the jaws A, B, and D, adjusting-screws *i* and *j*, and plane-bit *g*, arranged and operating with relation to each other, substantially as herein described, and for the purpose set forth.

FREDERICK RAUH.

Witnesses:

A. C. JOHNSON,
GEORGE HIRSCHINGER.