

W. H. WOOLARD.

FLOUR-BOLTS.





Hithesses: He Rydgreist. John Goethals 21.26. Wentor:

ATTORNEYS.

UNITED STATES PATENT OFFICE.

WILLIAM H. WOOLARD, OF WINDSOR, ILLINOIS.

IMPROVEMENT IN FLOUR-BOLTS.

Specification forming part of Letters Patent No. 182,142, dated September 12, 1876; application filed July 11, 1876.

To all whom it may concern:

Be it known that I, WILLIAM H. WOOL-ARD, of Windsor, in the county of Shelby and State of Illinois, have invented a new and Improved Dustless Reel-Head for Flour-Bolts, of which the following is a specification:

Figure 1 is a longitudinal section on line y y in Fig. 2. Fig. 2 is a transverse section on line x x in Fig. 1.

Similar letters of reference indicate corre-

sponding parts.

My invention consists in providing a stationary auxiliary head, carrying a packing of sheep's pelthaving the woolon, which is forced against the rotating head of the bolt-reel by means of springs, and retained in place by leather straps, the object being to prevent the accumulation of dust on the bolt-head, and to prevent the escape of specks and flour-dust from the bolt, and also to do away with the device used in flour-bolt chests commonly known as "speck-boxes."

A is an ordinary flour-bolt reel, having the head B, which is open in the center to receive the flour-spout C. E is the auxiliary head,

which is fitted over the spout C, and carries a packing, a, of sheep's pelt, the wool side of which presses against the head B. Two spiral springs, b, are attached to the frame which supports the bolt, and bear against the head D. Straps c, of leather or other suitable material, are fastened to the posts d, and also to the head D. The springs b and straps c support the head D in such a way that it adapts itself to the position of the bolt-head B as the bolt is raised or lowered.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

1. In combination with a flour-bolt, an auxiliary head, provided with a packing of wool or other similar material, and retained in place by suitable springs, substantially as shown and described.

2. The combination of the reel A, head D, packing a, springs b, straps c, and standards d, as shown and described.

WILLIAM H. WOOLARD.

Witnesses:

H. F. SMYSER, BENJAMIN FLOWERS.