

A. CHAMBERLIN.
SASH-FASTENER.

No. 191,403.

Patented May 29, 1877.

FIG. 1.





FIG. 2.



WITNESSES.

Geo. H. Carl.
B. S. Bryant

INVENTOR.

Albert Chamberlin
Per Brown Bros,
attorneys.

UNITED STATES PATENT OFFICE.

ALBERT CHAMBERLIN, OF NORTH ABINGTON, MASSACHUSETTS.

IMPROVEMENT IN SASH-FASTENERS.

Specification forming part of Letters Patent No. **191,403**, dated May 29, 1877; application filed February 21, 1877.

To all whom it may concern:

Be it known that I, ALBERT CHAMBERLIN, of North Abington, Plymouth county, State of Massachusetts, have invented a new and useful Improved Sash Holder and Fastener, of which the following is a specification:

My invention relates to certain improvements in sash-holders; and it consists of a novel construction and combination of parts, which will be fully hereinafter described, and specifically pointed out in the claim.

In the accompanying plate of drawings, Figure 1 is a vertical sectional view of a part of a sash and a window-frame having my improved sash holder and fastener applied; Fig. 2, a horizontal section on line *x x*, Fig. 1.

In the drawings, A represents a portion of a sash, and B a portion of the window-frame, against which runs the sash portion A; C, a lever hung on a fulcrum-pin, *a*, of the sash A, and adapted by its rubber-cushioned end *b* to bear against the surface *c* of the window-frame. This lever projects from the sash, and is then suitably formed to be operated by the thumb or finger. *d*, a spiral spring, fastened at one end to the upper side of the lever C, and at the other end to the sash above the lever C. The spiral spring *d* holds the rubber-cushioned end of the lever against the window-frame, and thus the sash is sustained in position when opened either wholly or partially.

To lower the sash, press at the outer end *f* of lever C, which draws the friction end of the lever from its bearing in the window-frame.

D is a stud on inner end of sash-lever C, and *l* a lip projection on the window-frame, lying across the recess *m* in the window-frame.

The recess *m* and the lip projection *l* are located in position for the recess to receive the lever C when the window is closed, and for the projection *l*, by the abutment against it of the stud D of the lever C, to prevent the window being raised except the lever be first suitably operated, to relieve it from its seat within the recess of the window-frame.

The friction or bearing end of the lever C allows the window to be raised as may be desired, offering no substantial obstruction thereto.

Having thus described my invention, what I claim, and desire to secure by Letters Patent, is—

The combination, with the lever C, having cushioned end *b* and spiral spring *d*, of the stud D, lip projection *l*, and recess *m*, and the window and sash frame, as described, for the purpose specified.

ALBERT CHAMBERLIN.

Witnesses:

EDWIN W. BROWN,
GEO. H. EARL.