


B. F. CARD.

ELECTRO-MAGNETIC REGISTERING APPARATUS FOR TURNSTILES.

No. 192,361.

Patented June 26, 1877.

Fig. 1.



Witnesses.
Charles B. Lee
Louis W. Frost



Inventor.
Benjamin F. Card

B. F. CARD.

ELECTRO-MAGNETIC REGISTERING APPARATUS FOR TURNSTILES.

No. 192,361.

Patented June 26, 1877.



Witnesses.
Charles B. Lee
Louis W. Frost

Inventor.

Benjamin F. Card.

UNITED STATES PATENT OFFICE

BENJAMIN F. CARD, OF BROOKLYN, NEW YORK.

IMPROVEMENT IN ELECTRO-MAGNETIC REGISTERING APPARATUS FOR TURNSTILES.

Specification forming part of Letters Patent No. **192,361**, dated June 26, 1877; application filed March 30, 1877.

To all whom it may concern:

Be it known that I, BENJAMIN F. CARD, of the city of Brooklyn, in the county of Kings and State of New York, have invented a new and useful Improvement in Electro-Magnetic Registering Apparatus and Turnstile; and that the following, taken in connection with the accompanying drawing, is a description of the same.

My improvement relates to the application of an electro-magnetic battery, in connection with suitable mechanical devices, and a suitable registering mechanism, for the purpose of registering the number of persons entering or leaving a bridge, ferry, hall, room, or other inclosure.

In the drawing, Figure 1 represents a plan or top view of my improvement, partly in section. Fig. 2 is a longitudinal vertical section. Fig. 3 is a side view of the dial-plate and its frame.

My invention is described as follows: At the entrance of the ferry, bridge, or inclosure is placed a turnstile consisting of a revolving vertical shaft, A, provided with four arms, b, so situated with regard to each other that a person entering from either side of the entrance shall push against one of said arms b and cause the shaft A to perform one-quarter of a revolution. The upper part of the shaft A passes through a suitable frame-work made so as to support a circular disk, B, of wood or metal, which turns loosely on shaft A. Directly above the disk B, and in contact with it, is a smaller circular disk, C, which is fixed to and turns with shaft A. This disk C has a portion of its periphery cut into cogged teeth, which engage with corresponding teeth of a pinion-wheel, c, which is vertically secured to the lower and larger disk B. The object of the cogged teeth on disk C and the pinion-wheel c is to prevent the registering mechanism, which will be hereinafter described, from registering until the shaft A has performed nearly one-quarter of a revolution, thus preventing the registering mechanism from acting on any slight movement of the shaft A, and doing away with any tendency to accidental registration.

The pinion-wheel c is provided also with a

pin, d, fixed horizontally to it, which pin d strikes against either of the two pins, d¹ or d², secured vertically to the disk C.

The object of these pins d d¹ d² is to save the cogs on the disk C and on pinion c from excessive strain or wear.

On the periphery of the large disk B, fixed horizontally, is a pin, e, which, as the disk B is made to revolve with shaft A, at every quarter of a revolution of shaft A, strikes against a button or circuit-closer, D, D¹, D², and D³, which are placed at proper distances apart and around the disk B. These circuit-closers are connected by a wire, f, with each other and with one of the poles, g, of a galvanic battery.

The disk B is connected with the other pole, h, of the battery, by means of the button or circuit-closer f, to which is connected the wire k, which passes through the electro-magnets G and G' and thence to the pole h.

Working in connection with the electro-magnets G and G' is the armature H, to which is secured a vertical lever, L. Attached to this lever L is one end of spring m, which has its other end secured to a standard, n. (See Fig. 2.) At the upper end of the vertical lever L are two pawls, O and P, one of which pawls, O, is secured to one side of the vertical lever L by screws or other suitable means, and the other pawl, P, is pivoted to said vertical lever L through a slot cut in its top, and is supported by a spring, p, placed under it.

These pawls engage with the teeth of the ratchet-wheel R. The object of these pawls O and P is to communicate a rotary motion to the ratchet-wheel R, and at the same time to prevent the ratchet-wheel R from moving more than the space of one of its teeth at one motion. The ratchet-wheel R is attached to a shaft, R', to which is fixed a registering index-hand, S, which moves around the face of a dial-plate, S', which dial-plate is furnished with a suitable index for registering the number of persons entering or leaving the ferry, bridge, or other inclosure. In connection with the ratchet-wheel R is a pawl, T, the purpose of which is to prevent the ratchet-wheel R from turning back after having moved the space of one of its teeth.

The shaft R' may be provided with a pinion, to which may be attached suitable mechanism for registering up to any number desired.

The operation of my invention is as follows: When a person enters the entrance-way where the turnstile is placed and attempts to pass the turnstile he imparts motion to the shaft A, and as he passes through causes it to perform one-fourth of a revolution. The movement of the shaft A turns with it the circular disk C, fixed to the shaft A. The motion of the disk C is communicated by means of the cogged teeth cut in, and one of the pins d^1 or d^2 fixed to said disk C, to the pin d on pinion-wheel c , secured to the disk B. The circular disk B is thus caused to revolve. This movement of the disk B causes the pin e , projecting horizontally from the circular disk B, to strike against one of the buttons or circuit-closers D, D^1 , D^2 , or D^3 , arranged at proper intervals around the disk B.

A current of electricity then immediately passes from the pole g of the galvanic battery through the wire f , and through the disk B and button F, and thence through the wire K to the electro-magnets G and G'. The passage of the current of electricity immediately causes these magnets G and G' to attract the armature H. The attraction of the armature H to the electro-magnets G and G' causes the lever L to move and the pawl P, connected with it, to engage with one of the teeth of the ratchet-wheel R, and to move the said ratchet-wheel R the space of one of its teeth, and imparts a rotary motion to said ratchet-wheel R.

The movement of the lever L also causes the pawl O to engage with the teeth of the ratchet-wheel R, and prevents it from moving more than the space of one of its teeth at one motion of the armature H and lever L. At the same time the movement of the pawl T prevents the ratchet-wheel R from turning back after having moved the space of one of its teeth.

The rotary motion of the ratchet-wheel R on its shaft or arbor R' causes the index-hand S to move over the face of the dial-plate S' and register.

By the above means a perfect and accurate automatic register is formed.

Having thus described my invention, what I claim is—

1. The shaft A and circular disk C, having a portion of its periphery cut with cog-teeth and provided with pins d^1 and d^2 , in combination with the circular disk B, provided with the pin d and pinion-wheel c , substantially as described.

2. A turnstile consisting of the shaft A and disks B and C, in combination with the magnets G and G', and connected therewith by means of a current of electricity passing through suitable circuit-closers, and actuating the armature H, pawls O, P, and T, lever L, ratchet-wheel R, and any suitable registering mechanism.

3. A turnstile consisting of shaft A and disks B and C, in combination with the magnets G and G', and connected therewith by means of a current of electricity passing through suitable circuit-closers, and actuating the armature H, pawls O, P, and T, lever L, ratchet-wheel R, index-hand S, and dial-plate S', substantially as described.

4. A turnstile consisting of the shaft A and disks B and C, in combination with the electro-magnets G and G', and connected therewith by means of a current of electricity passing through circuit-closers D, D^1 , D^2 , and D^3 , and pin e on disk B, and button F, and actuating the armature H, lever L, pawls O, P, and T, ratchet-wheel R, and any suitable registering mechanism.

5. A turnstile consisting of shaft A and disks B and C, in combination with the electro-magnets G and G', and connected therewith by means of a current of electricity passing through circuit-closers D, D^1 , D^2 , and D^3 , and pin e on disk B, and button F, and actuating the armature H, lever L, pawls O, P, and T, ratchet-wheel R, and any suitable registering mechanism.

In testimony that I claim the foregoing I have hereunto set my hand this 29th day of March, 1877.

BENJAMIN F. CARD.

In presence of—

CHARLES G. COE,
LOUIS W. FROST.