

H. PURDY.
FRUIT-JAR.

No. 192,453.

Patented June 26, 1877.

Fig. 1





Fig. 2



WITNESSES:

A. W. Aringqvist
J. H. Scarborough.

INVENTOR:

BY

H. C. Purdy.
Munnell
ATTORNEYS.

UNITED STATES PATENT OFFICE.

HIRAM PURDY, OF BURLINGTON, IOWA.

IMPROVEMENT IN FRUIT-JARS.

Specification forming part of Letters Patent No. **192,453**, dated June 26, 1877; application filed April 30, 1877.

To all whom it may concern:

Be it known that I, HIRAM PURDY, of Burlington, county of Des Moines, and State of Iowa, have invented a new and useful Improvement in Fruit-Jars, of which the following is a specification:

Figure 1 is a top view of a fruit-jar to which my improvement has been applied. Fig. 2 is a side view of the same, partly in section, through the line *x x*, Fig. 1, to show the construction.

The object of this invention is to furnish fruit-jars which shall be so constructed that they may be easily and quickly closed air-tight, and which may be conveniently opened when desired.

The invention will first be described in connection with the drawing, and then pointed out in the claim.

Similar letters of reference indicate corresponding parts.

A represents a fruit-jar the neck of which is beveled or tapered, and has a shallow groove, *a*¹, formed around it, to receive a packing, B, made of rubber or other suitable elastic material. Around the neck of the jar A, at about the middle of the groove *a*¹, is formed a narrow groove, *a*².

C is the cover or cap, the rim of which is beveled or flared to correspond with the bevel of the neck of the jar A, so that when the said cap C is pressed down upon the neck of the jar A its beveled rim may press the pack-

ing B snugly upon the said neck and form an air-tight joint. To further insure the joint between the cap and neck being air-tight a narrow bead or shoulder, *c*¹, is formed around the inner surface of the rim of the cap, to embed itself in the packing B and press it against the neck of the jar A. In the center of the cap C is formed a hole, *c*², to allow the air to escape while pressing the said cap down into place, and to allow the air to enter when the cap C is to be taken off.

The hole *c*² is closed by a rubber plug, D, which is pressed down into and is held in said hole *c*² by a band, E, of rubber or metal, which crosses the top of the cap C, and the ends of which have holes formed in them to receive the lugs or projections *a*³ formed upon the neck of the jar A. The corners of the cap C are notched to receive the band E and prevent it from having any lateral movement.

Having thus fully described my invention, I claim as new and desire to secure by Letters Patent—

The combination, with body A, having grooves *a*¹ *a*² and lugs *a*³, of the packing B, notched cover, having bead *c*¹, and the band E, having holes to receive said lugs, as and for the purpose specified.

HIRAM PURDY.

Witnesses:

JAMES T. GRAHAM,
C. SEDGWICK.