



M. A. CALDWELL.  
WRINGERS.

No. 193,688.

Patented July 31, 1877.



*Fig. 1.*



*Fig. 2.*

WITNESSES

Edwin James.  
John H. Jones

INVENTOR

Marvin A. Caldwell,  
per Sturgeon & Wallock  
Attorneys.

# UNITED STATES PATENT OFFICE.

MARVIN A. CALDWELL, OF NORTH EAST, PENNSYLVANIA.

## IMPROVEMENT IN WRINGERS.

Specification forming part of Letters Patent No. **193,688**, dated July 31, 1877; application filed August 28, 1876.

*To all whom it may concern:*

Be it known that I, MARVIN A. CALDWELL, of North East, in the county of Erie and State of Pennsylvania, have invented a new and useful Improved Clothes-Wringer; and I do hereby declare the following to be a full, clear, and exact description thereof.

My invention consists in providing certain new and useful improvements in the construction of clothes-wringers.

The nature of my invention consists in the construction and arrangement of a clothes-wringer and its frame-work, so that part of the said frame-work shall serve as standards, to support a vat for water to be used in washing, which is attached solidly thereto, and also in the arrangement of the parts which operate said wringer.

The device is shown in the accompanying drawings, as follows:

Figure 1 is an end-view elevation, and Fig. 2 is a side-view elevation.

The parts of the device are as follows: A is the box or vat, which serves as a tub, in which the washing is done. This is supported on legs B B, which, at the end at which the wringer is used, are so extended as to serve as part of the frame-work of the wringing device—that is, they form the uprights of the wringer. This arrangement gives strength to the frame and to the whole device, and enables me to better connect and use the treadle or tension devices.

The parts of the wringer are as follows: J J' are the expressing-rollers, which are constructed in the usual manner, and are operated as usual. The tension of these rollers is obtained by the levers Q R, which are connected together and to a yoke, S, by links q r. The yoke S is formed of a bar and links s s, which loop over the upper roller.

The levers are operated by a treadle, P, or by a hand-lever, O, as may be desired; or both methods may be used on the same machine, which will often be found convenient, for when the hand-lever is used it can be retained depressed at any point by the ratchet N, and when any extra pressure is wanted it can be given by the foot-lever.

What I claim as my invention, and desire to secure by Letters Patent, is as follows:

1. The combination, in a wringing-machine, of the uprights formed of the legs B B of the vat A, yoke and links S s s, levers Q R, and links q r, and lever O or P, substantially as shown and described.

2. The combination, in a wringing-machine, of rollers J J', yoke and links S s s, levers R and links q r, and levers O or P, substantially as set forth.

In testimony whereof I, the said MARVIN A. CALDWELL, have hereunto set my hand.

MARVIN A. CALDWELL.

Witnesses:

JNO. K. HALLACK,

ROBERT H. PORTER.