



G. STRIBLEY.
Seams for Boots and Shoes.

No. 196,720.

Patented Oct. 30, 1877.



Attest

Edgar Jones
John E. Jones

Inventor

George Stribley
By F. Millward
Attorney

UNITED STATES PATENT OFFICE.

GEORGE STRIBLEY, OF CINCINNATI, OHIO.

IMPROVEMENT IN SEAMS FOR BOOTS AND SHOES.

Specification forming part of Letters Patent No. **196,720**, dated October 30, 1877; application filed July 28, 1877.

To all whom it may concern:

Be it known that I, GEORGE STRIBLEY, of Cincinnati, Hamilton county, State of Ohio, have invented an Improvement in the Manufacture of Boots and Shoes, of which the following is a specification:

My invention relates to that class of boots and shoes in which a narrow strip of leather is used to strengthen the seam which joins the two sides or quarters at the back; and my invention consists in a new way of securing the quarters in connection with said strip.

In the accompanying drawings, Figure 1 is a perspective view of the quarters joined to form a heel-seam by my improved method, the seam being partly opened to expose the method of formation. Fig. 2 is a section of the heel-strip and quarters at the termination of the first step in the process. Fig. 3 is a similar section when the seam is completed.

A B represent the quarters, and C the heel-strip. I attach the heel-strip C, in the manner shown in Fig. 2, by two rows of stitching, $x x'$, near the edges, the stitching through the quarters being at such distance inside of their edges as to leave laps $a b$ nearly equal to the width of the heel-strip, and the stitching being made in turned edges of the heel-seam, as shown, so that they are blind-stitches when the seam is completed. To complete the seam, I fold over the laps, as shown in Fig. 3, and make two rows of stitching, $y y'$, through all three thicknesses, these rows being inside of the blind-stitching, as shown.

This method gives three thicknesses of material to form and strengthen the heel-seam, and its through-and-through stitches $y y'$ are fully protected from wear or strain by the presence of the stitches $x x'$ outside of them.

Changes may be made from this exact construction without departing from the essential features of my invention—as, for example, the lap b may be a little shorter than is shown, so that the stitching y may not have to pass through it.

I claim—

1. The above-described method of connecting the sides, fronts, or quarters, and seam-stays of boots and shoes, by attaching the strip by blind-stitching, so as to leave overlaps on the sides, folding the overlaps one upon the other, and both upon the stay-piece, and then securing them by two rows of through-and-through stitching immediately inside of the blind-stitching, substantially as specified.

2. The improved article of manufacture herein described, consisting of a boot or shoe having a seam formed by a strip secured by blind-stitching and flaps on the respective parts to be united, which flaps are folded upon each other and upon the strip, and are secured by through-and-through stitching.

In testimony of which invention I hereunto set my hand.

GEORGE STRIBLEY.

Witnesses:

JOHN E. JONES,
WM. M. KEPLER.