

S. S. LELAND.

Halter.

No. 206,586.

Patented July 30, 1878.

Fig. 1




Fig. 2




Fig. 4




Fig. 3





Fig. 5



Attest:

A. Barthel
Charles J. Hunt

Inventor:

S. S. Leland
By Atty
Thos. S. Sprague

UNITED STATES PATENT OFFICE.

SOMERS S. LELAND, OF QUINCY, MICHIGAN.

IMPROVEMENT IN HALTERS.

Specification forming part of Letters Patent No. **206,586**, dated July 30, 1878; application filed June 19, 1878.

To all whom it may concern:

Be it known that I, SOMERS S. LELAND, of Quincy, in the county of Branch and State of Michigan, have invented an Improvement in Halters, of which the following is a specification:

The nature of this invention relates to an improvement in the construction of halters; and the invention consists, first, in the peculiar slotted fastening-plate; and, second, in the peculiar halter composed of a continuous strap, a ring, and a slotted plate, as fully hereinafter explained.

Figure 1 represents my improved halter as adjusted to a horse. Fig. 2 is a plan view of the fastening-plate. Fig. 3 is an enlarged perspective of the strap, ring, and fastening-plate. Fig. 4 is a perspective view, showing a strap adjusted to prevent the ring from slipping. Fig. 5 is a section on line *xx*, in Fig. 4.

In the accompanying drawings, which form a part of this specification, A represents a metallic plate, in which are cut the two slots *a*, which are provided with the studs *b*.

A strap, B, of leather or other suitable material, has one end secured in one of the slots *a*, a hole in said strap engaging with one of the studs *b*. The strap is carried forward through a ring, C, and back, forming the nose-noose *c*, thence upward and back through the ring, forming the head-noose *d*, to the slot *a*,

upon the opposite side of the plate A, where it is secured, as before described, the remaining portion of the strap serving as a tie-strap.

If desired, sliding metallic loop-bands *f* may be put upon the sides of the nose and head-loops, and be connected together by cheek-straps D, which will retain the nose-loop in its proper position upon the nose of the animal wearing the halter.

After the halter has been adjusted to fit a certain animal, if desired, a small strap, E, may be passed through the ring C, and secured in the slots *b* of the plate A, which will keep the parts in their relative positions as adjusted.

By this manner of constructing a halter a great amount of labor and material is saved.

What I claim as my invention is—

1. In a halter composed of a continuous strap, the fastening-plate A, having slots *a* and studs *b*, to which the ends of such strap are secured, substantially as described and shown.

2. A halter composed of the continuous strap B, ring C, and plate A, provided with the slots *a* and studs *b*, substantially as and for the purpose specified.

SOMERS S. LELAND.

Witnesses:

H. S. SPRAGUE,
THEO. S. DAY.