

W. I. WINNE.
Box-Fastener.

No. 212,079.

Patented Feb. 4, 1879.




FIG. 3.




FIG. 1.




FIG. 4.




FIG. 2.

Witnesses.
William H. Low.
E. J. Benham.

Inventor
William I. Winne

UNITED STATES PATENT OFFICE.

WILLIAM I. WINNE, OF ALBANY, NEW YORK.

IMPROVEMENT IN BOX-FASTENERS.

Specification forming part of Letters Patent No. **212,079**, dated February 4, 1879; application filed November 9, 1877.

To all whom it may concern:

Be it known that I, WILLIAM I. WINNE, of the city and county of Albany, and State of New York, have invented certain new and useful Improvements in Fastening Devices for the Covers of Boxes, &c., of which the following is a full and exact description:

My invention relates to certain improvements on the fastening device for which Letters Patent of the United States, No. 195,874, were granted to me on the 2d day of October, 1877; and it consists in forming in one of the limbs of the device an eye, which passes entirely around the locking-staple, thereby rendering the device useful as a hasp for a padlock.

In the accompanying drawings, which form a part of this specification, Figure 1 is a side elevation of one form of my device, and Fig. 2 a front elevation of same; Fig. 3, a side elevation of a modification of it, and Fig. 4 a front elevation of same.

As shown in the drawings, the fastening is made of a metallic bar, preferably of wire, having sufficient elasticity to form a spring, bent at A to form a bight, which is secured by the staple *a* to the cover. The two parts are bent at *b* to form the limbs B B', which extend downward at the side of the box. The limb B is bent at *c* to form a hook, C, which, as

shown in Fig. 4, extends out in a straight line; but, as shown in Fig. 2, it is made with a return-bend at *c'*, to form a bight for holding a seal, padlock, or other device for preventing the hook from being withdrawn from its staple D. The other limb, B', is given a counter-bend at *c''*, to form an eye, which passes entirely around the base of the staple D.

When desirable to do so, either modification shown in the drawings may be used in conjunction with a padlock, by simply withdrawing the hook C from the staple D and resting it on the crown of the staple, the hinged link of the padlock being passed in its stead through the staple D. When used in this manner the fastening serves the purpose of a padlock-hasps.

I claim as my invention—

The combination of the staple D with the improved fastening device herein described, consisting of a metallic bar bent to form the limbs B B', extending to the staple D, one of said limbs being provided with a hook, C, the other limb being bent to entirely surround said staple, to serve as a hasp, as and for the purpose herein specified.

WILLIAM I. WINNE.

Witnesses:

WILLIAM H. LOW,
E. F. BENHAM.