


A. W. SOUTHARD & V. R. SEARS.
Invalid-Bed.

No. 212,757.

Patented Feb. 25, 1879.



WITNESSES:

Francis McArdle,
J. H. Scarborough.

INVENTOR'S

A. W. Southard.
V. R. Sears.
BY *Wm. H. Hunt*

ATTORNEYS.

UNITED STATES PATENT OFFICE.

ALFRED W. SOUTHARD AND VOLNEY R. SEARS, OF FALLS CITY, NEBR.

IMPROVEMENT IN INVALID-BEDS.

Specification forming part of Letters Patent No. **212,757**, dated February 25, 1879; application filed September 29, 1877.

To all whom it may concern:

Be it known that we, ALFRED WILLIAM SOUTHARD and VOLNEY RUFUS SEARS, of Falls City, in the county of Richardson and State of Nebraska, have invented a new and useful Improvement in Invalid-Beds, of which the following is a specification:

Figure 1 is a vertical longitudinal section taken through the line *x x*, Fig. 2. Fig. 2 is a vertical cross-section of the same, taken through the line *y y*, Fig. 1. Fig. 3 is a detail view in elevation.

Similar letters of reference indicate corresponding parts.

The invention will first be described in connection with the drawings, and then pointed out in the claim.

A is the frame, which is formed of four posts, connected at their upper and lower ends by bars, and strengthened at the upper side corners by braces.

B are bars that support a flag-staff, C, and D the frame of bedstead, having feet E and cross-slats F H, to which are attached springs G and short bars I. J are tie-rods, and K are connecting-straps, while L represents the mattress. To the end bars of the bedstead-frame D are attached four cords, M, that are passed through holes in the ends of short blocks N, over the pulleys O, and then through holes in the other ends of said blocks, being knotted to prevent them from drawing out. The cords M and blocks N enable the bed to

be readily adjusted at any desired height, when the friction of the blocks upon the cords will hold it securely in place.

To the top side bars of the frame A, near their foot ends, are detachably attached the ends of a cross-bar, T, to the end parts of which are attached by tenons and keys, or other conveniently-detachable means, the upper ends of two bars, U. To the lower ends of the bars U are hinged the upper ends of two short bars, V, to the lower ends of which are attached the ends of a cross-bar, W. The bar W is padded, and is designed to support the leg of an invalid while having a surgical operation performed upon it or having it dressed.

When not in use the bar W may be turned up out of the way, and when not required for use the whole device T U V W may be detached and taken away.

Having thus described our invention, we claim as new and desire to secure by Letters Patent—

The combination of the cross-bar T, the hanging bars U, the hinged bars V, and the cross-bar W with the frame that surrounds the bed, substantially as shown and described, for the purpose specified.

ALFRED WILLIAM SOUTHARD.

VOLNEY RUFUS SEARS.

Witnesses:

CHARLES H. RICHARDS,
EZRA E. METZ.