


L. J. CARPENTER.
Spinning-Top.

No. 214,023.

Patented April 8, 1879.



Witnesses.

E. A. McNaughton
A. J. Sangster

Inventor

Lewis J. Carpenter
By James Sangster
Atty.

UNITED STATES PATENT OFFICE

LEWIS J. CARPENTER, OF BUFFALO, NEW YORK, ASSIGNOR TO ESTELLE E. McNAUGHTON, OF CLEVELAND, OHIO.

IMPROVEMENT IN SPINNING-TOPS.

Specification forming part of Letters Patent No. 214,023, dated April 8, 1879; application filed February 6, 1879.

To all whom it may concern:

Be it known that I, LEWIS J. CARPENTER, of the city of Buffalo, in the county of Erie and State of New York, have invented certain new and useful Improvements in Spinning-Tops, which improvements are fully set forth in the following specification and accompanying drawings, in which—

Figure 1 represents a side elevation; Fig. 2, a plan view; Fig. 3, a vertical central section through the top in line X X, Fig. 2, and a similar section through the holding-piece, also a side elevation of the spinning-screw; and Fig. 4 is a top view of the holding-piece.

The object of this invention is to produce a self-winding top; and it consists of a top having a hollow spindle, provided with a suitable opening to receive a screw of long lead, in combination with a tubular holding-piece arranged so as to keep the top in the proper position for receiving a spinning movement while the screw is being quickly withdrawn, as will be more clearly understood by reference to the drawings, in which—

A represents the body of the top; B, the hollow spindle, having a slot or opening, C, of the same width and thickness as the screw

D, which, as shown in the drawings, is made of a slip of flat twisted metal, but may be a screw of two or more threads, so as to give it the necessary lead. The opening C is made large enough so that the screw, if entered, will revolve or turn down by its own weight.

E is a knob or handle for holding the screw. F represents a holding-piece. It is provided with a flange, G, for the fingers to rest against while the screw D is being withdrawn to spin the top, which drops away from the holding-piece as soon as the screw leaves it.

In spinning the top, the part F, which is a tube having a flange, G, is put on the tube or spindle B, and the screw inserted, as shown in Fig. 3. The part F is held firmly in the hand while the screw is quickly withdrawn, thereby causing the top to drop and spin.

I claim as my invention—

A spinning-top having a hollow spindle, B, provided with an opening, C, in combination with a screw, D, and holding-piece F, as and for the purposes described.

LEWIS J. CARPENTER.

Witnesses:

A. J. SANGSTER,
JAMES SANGSTER.