


(No Model.)

F. H. BROWN.
Oscillating Cradle.

No. 236,545.

Patented Jan. 11, 1881.



Witnesses
Fred G. Dieterich
Albert H. Krause.

Inventor:
Fred Harvey Brown
by Louis Baggett
his attorney

UNITED STATES PATENT OFFICE.

FRED. H. BROWN, OF FORT WORTH, TEXAS, ASSIGNOR TO MAX ELSER
AND JOHN PERRY ALEXANDER, OF SAME PLACE.

OSCILLATING CRADLE.

SPECIFICATION forming part of Letters Patent No. 236,545, dated January 11, 1881.

Application filed August 18, 1880. (No model.)

To all whom it may concern:

Be it known that I, FRED. H. BROWN, of Fort Worth, in the county of Tarrant and State of Texas, have invented certain new and
5 useful Improvements in Oscillating Cradles; and I do hereby declare that the following is a full, clear, and exact description of the invention, which will enable others skilled in the art to which it appertains to make and use the
10 same, reference being had to the accompanying drawing, which forms a part of this specification, and in which I have represented my improved crib in side elevation.

My invention has relation to oscillating cribs
15 or cradles operated by clock-work or similar mechanism; and it consists in the detailed construction and combination of parts as hereinafter set forth, and particularly pointed out in the claim.

20 A represents the frame of the crib, which may be of light wood-work, wicker-work, or similar suitable material, and should be provided with one or more wire arches, B, for supporting a mosquito-canopy, when desired.
25 On opposite sides of the frame A are two cross-bars, C, (only one of which is shown in the drawing,) in which the pendulum-bars D D (two on each side) are pivoted at *a a*. Attached to the lower end of these bars are adjustable weights E E, which may be fixed in
30 their position upon their respective bars by means of set-screws *e e*. The upper end of each of the pendulum-bars D D are pivoted in the upper side rails of the crib I at *b b*.

35 F is a pitman, which extends from one of the bars D to the crank G of a clock-work mechanism, H, of suitable construction, which may be operated by weights or springs, as preferred. By the rotation of crank G the
40 pitman F is reciprocated, thus vibrating that one of the pendulum-bars to which it is at-

tached, and with it the crib, which is supported upon and between the four bars, above their point of connection with the cross-bars C.

By adjusting the weights or pendulums E 45 upon their respective bars the weight of the crib and child may be balanced so as to work easily and smoothly within the frame.

Attached to the bottom of the crib is a slender rod, I', which has a round wooden head, 50 *i*, at its lower end, that plays upon a xylophone or metallophone, K, placed in the frame underneath the crib, during its vibrations to and fro.

This crib is simple and compact in its construction, works easily and without noise, except that of the xylophone, which is of a pleasing character, calculated to soothe the child and encourage sleep.

Having thus described my invention, I claim 60 and desire to secure by Letters Patent of the United States—

The improved mechanical crib herein described, composed of the frame or support A, having cross-bars C, pivoted pendulum-bars 65 D, having adjustable weights E, crib I, supported upon and suspended between said bars above their point of connection with the cross-bar C, and provided with the flexible rod I', pitman F, clock mechanism H, having crank 70 G, and the musical instrument K, all constructed and combined to operate substantially in the manner and for the purpose herein shown and specified.

In testimony that I claim the foregoing as 75 my own I have hereto affixed my signature in presence of two witnesses.

FRED. HARVEY BROWN.

Witnesses:

S. SEATON,
LEVI W. NORCROSS.