J. A. MALONEY. Pantaloon Protector.

No. 238,046.

Patented Feb. 22, 1881.

FIG. I.




FIG. IV.

WITNESSES.

L. J. Maloney

James et Maloury

United States Patent Office.

JAMES A. MALONEY, OF GEORGETOWN, ASSIGNOR, BY MESNE ASSIGNMENT, OF ONE-HALF TO GEO. T. KEEN, OF WASHINGTON, D. C.

PANTALOON-PROTECTOR.

SPECIFICATION forming part of Letters Patent No. 238,046, dated February 22, 1881.

Application filed September 18, 1880. (Model.)

To all whom it may concern:

Be it known that I, James A. Maloney, of Georgetown, in the county of Washington and District of Columbia, have invented cer-5 tain new and useful Improvements in Pantaloon-Protectors; and I do hereby declare that the following is a full, clear, and exact description of the invention, which will enable others skilled in the art to which it apperto tains to make and use the same, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form a part of this specification.

My invention relates to an improved method 15 and means for protecting pantaloons against | wear by reason of their coming in contact with

the ground in walking.

In the drawings, Figure I is a front view of my improved protector; Fig. II, a sectional 20 view. Figs. III and IV represent a modification of my invention.

A represents the body of the protector; B, a bead or cord at the base of the protector; E, metallic fasteners for applying the protector 25 to pantaloons. a a are openings for sewing

the protector to pantaloons.

The protector is applied as follows: The end of the pantaloons-leg is allowed to rest on the bead or cord B, as shown by the dotted 30 lines in Figs. II and III, and in the case of a fastener being used it is passed between the cloth and facing and then bent down so as to hold the protector in position.

When it is desired to fasten the protector 35 by sewing, I have provided openings a a to receive the thread. Said openings are connected with each other by a channel, a', upon the side of the web opposite to the cord or bead, into which the thread used in sewing is al-40 lowed to rest, to prevent its being cut by constant rubbing against the boot or shoe. The channel may be made deep enough to admit of sewing without the aid of openings a a.

The protector may be made of any wear-resisting material; but I prefer, in practice, to 45 use rubber, or rubber and a textile fabric combined. In order to prevent the rubber, by reason of its contact with the boot or shoe, wearing off the surface of the leather, I propose to have that side of the protector either flocked 50 or faced with any desirable fabric.

My protector will supply a want long needed, inasmuch as it is made very cheaply, is almost invisible when attached to pantaloons, and tends to preserve the shape of the pantaloons 55

better than the forms now in use.

Many persons will cast aside a comparatively good pair of pantaloons simply because the end of the legs has frayed out and worn away by dragging upon the sidewalk, and as 60 there is no way of repairing, save by shortening the legs of pantaloons, the advantages of my improvement become at once apparent.

Having described my invention, what I claim as new, and desire to secure by Letters 65

Patent, is—

1. In a protector for pantaloons, the combination of a web or fin, having a channel for the admission of thread, with a cord or bead arranged upon the edge of the web or fin op- 70 posite to the channel side, substantially as and

for the purpose set forth.

2. In a protector for pantaloons, the combination of a web or fin having a channel for the admission of thread, a cord or bead ar- 75 ranged upon the edge opposite to the side upon which the channel is placed, and a facing of textile fabricupon said web or fin, substantially as described, and for the purpose set forth.

In testimony that I claim the foregoing as my own I affix my signature in presence of two witnesses.

80

Witnesses: JAMES A. MALONEY.

J. M. YZNAGA, A. G. HEYLMUN.