

(No Model.)





2 Sheets—Sheet 1.

A. S. NEWBY.

CENTER PIECE FOR COOKING STOVES.

No. 246,809.

Patented Sept. 6, 1881.



WITNESSES
E. H. Bates
Phillips

INVENTOR
A. S. Newby
by Adamson Smith
his ATTORNEYS

(No Model.)


2 Sheets—Sheet 2.

A. S. NEWBY.

CENTER PIECE FOR COOKING STOVES.

No. 246,809.

Patented Sept. 6, 1881.



WITNESSES
E. J. Bates
James J. Sheehy

INVENTOR
Albert S. Newby.
by Anderson Smith
his ATTORNEYS

UNITED STATES PATENT OFFICE.

ALBERT S. NEWBY, OF CHAMPAIGN, ILLINOIS.

CENTER PIECE FOR COOKING-STOVES.

SPECIFICATION forming part of Letters Patent No. 246,809, dated September 6, 1881.

Application filed May 19, 1881. (No model.)

To all whom it may concern:

Be it known that I, ALBERT S. NEWBY, a citizen of the United States, resident at Champaign, in the county of Champaign and State of Illinois, have invented a new and valuable Improvement in Center Pieces for Stoves; and I do hereby declare that the following is a full, clear, and exact description of the construction and operation of the same, reference being had to the annexed drawings, making a part of this specification, and to the letters and figures of reference marked thereon.

Figure 1 of the drawings is a representation of a top view of the parts disconnected. Fig. 2 is a perspective view of the support or leg, and Fig. 3 is a sectional view of the same. Fig. 4 is a detail view of the support in connection with the top, and Fig. 5 is a vertical sectional view of the center plate in connection with the outer and inner attachments.

This invention has relation to the tops of cooking-stoves and ranges; and it consists in the construction and novel arrangement of the slotted center and its adjoining adjustable plates engaging therewith.

It also consists in the combination, with the center and its slotted tongues, of the adjoining adjustable plates, having recesses and perforations for connection with said tongues, as hereinafter shown and described.

In the accompanying drawings the letter A designates the center plate proper, having the four concave sides *a* and the usual supporting-ledges formed thereon. From this center plate extend outward the depressed tongues *b*, which are provided each with a slot, *c*, in the direction of its length. These depressed tongues are usually formed only on three of the projecting portions or corners of the center plate, while the fourth corner or projecting part is cast with an angular notch, *d*, having a depressed supporting-ledge, as shown in the drawings.

E designates one of the adjacent outer and shorter plates, which are designed to connect with the center plate, A, in filling the intermediate space of the stove top, and completing the circular bearings for the pots and lids.

Three of these are of the usual triangular form, having supporting-ledges on their concave sides *e*; but between the ends of these concave sides a recess, *g*, is formed to receive the tongues *b* of the center plate, and perforations *h* are provided for the passage of a bolt or rivet-stud designed to connect the outer plate to the center.

It will also be observed that a tongue, *h'*, is formed on the outer plate, E, which is designed to extend over the root of the tongue *b* of the center plate, so as to form a long and secure bearing. These plates may be adjusted with reference to each other through the medium of the slotted tongue-connections, so that the resulting combination or stove-top center will fit within reasonable limits stoves of various sizes.

K represents the separate outer plate or casting, having an angular end, *l*, projecting from between its sides, and designed to rest on the V-shaped supporting-ledge of the center plate above described.

Usually it is desirable to support the main center plate, and for this purpose the hollow supporting post or leg N is employed. This consists of two concave sections, *s* and *t*, the former being provided with a slotted arm, *z*, whereby it may be bolted to the center plate. The latter section, *t*, is slotted at *m*, and is adjustably connected to the section *s* by a bolt, *r*, which also passes through the slot *m'* of the section *s* and is secured by a nut. The sections are joined at their edges *v*, which are serrated, so that they can be interlocked securely after the post has been adjusted to the required height. The hollow post thus formed is thoroughly ventilated, and, although of comparatively thin material, will not be burned out by the action of the fire in the stove.

What I claim, and desire to secure by Letters Patent, is—

1. The perforated outer plates, E, and the center plate, A, having the slotted tongues *b* for engagement with said perforated outer plates, substantially as specified.

2. The center plate, A, having the slotted tongues *b*, and the V-shaped ledge, in combi-

nation with the perforated outer plates, E, and the plate K, having the angular end *l*, substantially as specified.

3. The adjustable ventilated support N, consisting of the sections *s* and *t*, connected by bolt, and having an attachment-arm, *z*, on the former section, substantially as specified.

In testimony that I claim the above I have hereunto subscribed my name in the presence of two witnesses.

ALBERT S. NEWBY.

Witnesses:

ALEX. JOLLY,
GEO. L. MAXWELL.