(Model.)

No. 256,617.

W. A. BAKER.

WAGON YOKE.

Patented Apr. 18, 1882.



WITNESSES:

Theo. J. Hoston. 6. Sedquick

N. PETERS, Photo-Lithographer, Washington, D. C.

. .



UNITED STATES PATENT OFFICE.

Eo

WILLIAM A. BAKER, OF COLOMA, MICHIGAN.

WAGON-YOKE.

- • -

SPECIFICATION forming part of Letters Patent No. 256,617, dated April 18, 1882.

Application filed August 15, 1881. (Model.)

To all whom it may concern:

Be it known that I, WILLIAM A. BAKER, of Coloma, in the county of Berrien and State of Michigan, have invented a new and useful Im-5 provement in Wagon-Yokes, of which the following is a full, clear, and exact specification. ·It is now the practice to support the tongues of wagons upon the necks of the horses by straps leading from the end of the tongue or from the ro ends of the neck-yoke to rings in the hames of the harness. This method of supporting the tongue interferes with the free action of the horses, and, if the horses are to be used singly as well as in span, necessitates the keeping 15 on hand of two sets of harness or much changing of straps, &c., of the double harness to adapt it both for single and double use, which is a great trouble and annoyance. By my invention the same harness may be 20 used both for single and double driving without much changing of straps, and the tongue of the wagon is made shorter, so as to occupy less space in turning, and all weight is removed from the necks of the horses and all 25 rigging is removed from in front of their breasts and necks. My invention consists in supporting the tongue upon a yoke under the horses, said yoke being suspended from straps attached to the 30 back-pads of the harnesses. In the accompanying drawings, Figure 1 shows a plan view, and Fig. 2 a section on the line x x, of my invention. Similar letters of reference indicate corre-35 sponding parts. In the drawings, A represents the wagon tongue or pole, and B represents the yoke, which latter is adapted to be suspended under the horses, under the belly bands of the har-40 nesses, and preferably from straps attached to the back-pads of the harness. The yoke is preferably flattened upon its upper side, and I

the tongue is secured upon the yoke by the pivot a, and it is provided with the mortises c, four in number, so arranged as to come upon 45 the sides of the horses. In these mortises are placed the cross-pins c', to which are secured the straps d d, by means of which the yoke is buckled to the straps of the back-pads, which usually support the thills of single wagons, or, 50 rather, the straps through which the thills pass; or separate straps may be used, which pass over the backs of the horses; and in these mortises are also buckled the holdback-straps f, which buckle or snap into the rings of the 55 breeching of the harness, as shown in Fig. 1. By this arrangement it will be understood that the tongue of the wagon may be much shorter than when the ordinary neck-yoke is used, and that all weight is taken from the necks of the 60 horses, and that there will be no rigging in front of their breasts, and that the same harness may be used for both double and single driving without much changing of straps. Having thus fully described my invention, I 65 claim as new and desire to secure by Letters Patent— 1. An improved yoke for supporting tongues of wagons, adapted to be suspended under the horses from the back-pads, substantially 70 as and for the purpose set forth. 2. The yoke B, formed with the slots c, and provided with the pins c', whereby the straps $\overline{d} d$ and the holdback-straps f f may be at- \cdot tached to it, substantially as and for the pur-75 poses set forth. 3. The combination, with the short pole A, of the yoke B, pivoted to the said pole and provided with the straps d f, substantially as and for the purpose set forth. WILLIAM ALLEN BAKER.

Witnesses: FRED. R. BOYD, S. SHOUP.

and a second second