
## C. C. BRAMOW.

QUILTING FRAME.

No. 257,283.

Patented May 2, 1882.



James J. Sheely.

Enderson Smith ATTORNEYS

## United States Patent Office.

CHRISTOPHER C. BRAMOW, OF RACINE, WISCONSIN.

## QUILTING-FRAME.

SPECIFICATION forming part of Letters Patent No. 257,283, dated May 2, 1882.

Application filed August 23, 1881. (Model.)

To all whom it may concern:

Be it known that I, Christopher C. Bramow, a citizen of the United States, resident at Racine, in the county of Racine and State of Wisconsin, have invented a new and valuable Improvement in Quilting-Frames; and I do hereby declare that the following is a full, clear, and exact description of the construction and operation of the same, reference being had to the annexed drawings, making a part of this specification, and to the letters and figures of reference marked thereon.

Figure 1 of the drawings is a representation of a cross-section of my invention, and Fig.

15 2 is a plan view.

This invention has relation to quiltingframes; and it consists in the novel construction and arrangement of a corner-bracket comprising a double angular socket and a sleeve 20 and binding screws for the horizontal socket and sleeve and the adjusting and winding rods, as will be hereinafter fully described, and pointed out in the claim.

Referring by letter to the accompanying 25 drawings, A designates the corner-bracket. which I employ to connect the rails, rods, and legs of my quilting-frame. The bracket consists of the vertical socket B and the horizontal socket C, having a set-screw, D. The sockets 30 B and C are at right angles to each other, and a horizontal sleeve, E, having a set-screw, F, is secured at the junction of the sockets B and C at right angles thereto. The socket C and sleeve E are in the same horizontal plane. 35 Four of these corner-brackets are used in connecting the legs G, winding-rails H, and adjusting rails I to form the quilting-frame. The legs G have their upper ends driven into the vertical socket B, and are there secured by a 40 pin or otherwise. The winding-rails H have

their rounded ends inserted in the horizontal sockets C, and are held in place by the setscrews D.

The adjusting-rails I are rounded for about two thirds of their length, the central portion 45 being left square, preferably; but this form is

not essentially necessary.

It will be seen that the winding-rails may be moved nearer to each other when it becomes necessary by loosening the set-screws F and 50 sliding the sleeves E inwardly upon the adjusting-rails I and then tightening the set-screws F to hold the frame firmly.

This frame may be easily taken apart for storage or transportation, and is cheap, con- 55

venient, and durable.

Adjusting-rails in a quilting-frame on which the winding-rails may be advanced or receded, as necessity requires, are not new; neither are set-screws for securing the rails to their ad- 60 justments. I do not claim either broadly, but ask protection only for the construction hereinafter specifically claimed.

Having thus described my invention, what I claim as new, and desire to secure by Letters 65

Patent, is—

In a quilting-frame, the combination of the legs G, winding-rails H, and adjusting-rails I, with the corner-brackets A, composed of the sockets B and C, sleeve E, and set-screws D 70 and F, substantially as and for the purposes set forth.

In testimony that I claim the above I have hereupto subscribed my name in the presence of two witnesses.

CHRISTOPHER C. BRAMOW.

Witnesses:

C. F. HART,

O. F. Botsford.