

(No Model.)

O. PEDERSON.

CASTER.

No. 266,509.

Patented Oct. 24, 1882.

Fig. 2.






Fig. 1.



Attest;
H. B. Applewhite,
E. J. Redmond.

Fig. 3.



Inventor;
Ole Pederson.
per atty.
A. H. Evans & Co

UNITED STATES PATENT OFFICE.

OLE PEDERSON, OF COLUMBUS, OHIO, ASSIGNOR TO ROBERT G. JORDAN
AND DAVID C. MEEHAN, OF SAME PLACE.

CASTER.

SPECIFICATION forming part of Letters Patent No. 266,509, dated October 24, 1882.

Application filed September 1, 1882. (No model.)

To all whom it may concern:

Be it known that I, OLE PEDERSON, of Columbus, in the county of Franklin and State of Ohio, have invented certain new and useful
5 Improvements in Furniture-Casters; and I do hereby declare the following to be a full, clear, and exact description of the same, reference being had to the accompanying drawings, making a part of this specification, in which—

10 Figure 1 is an elevation of a caster partially in section with my improvements attached. Fig. 2 is a section of the same through *x x* of Fig. 1. Fig. 3 is a view of the shank detached from the pivot-bar.

15 My invention relates to certain improvements in furniture-casters, and is an improvement on my Patent No. 218,565, issued to me August 12, 1879; and it consists in the arrangement and combination of devices hereinafter
20 explained and claimed.

To enable others skilled in the art to make and use my invention, I will proceed to describe the exact manner in which I have carried it out.

25 Referring to the drawings, A A are the ground-rollers of the caster. B B are the conical pivots carrying the rollers A A. C is the shank of the caster, and D its vertical extension. The pivots B B are rigidly united by
30 the rectangular connecting-bar *a*, cast solid with the pivots and with the flanges or washers *b b*.

In my patent above referred to I describe and claim the rollers as first cast and cleaned,
35 and then set up in the mold in which the shank of the caster is to be cast, allowing the liquid metal to form the shank, and at the same time to flow through the eyes of the rollers A A, thus making the shank and pivots in one
40 solid piece, which I find from experience to be a difficult and costly method of construction. To overcome this difficulty is the object of my present invention, in which I cast and finish
45 up each of the several parts of my caster separately, and then put them together, as hereinafter explained.

The pivots B B are cast solid with the connecting-bar *a* and flanges *b b*, the central portion, *a*, between the washers being cast
50 nearly rectangular in cross-section, as shown

in Fig. 2. The shank C is formed with a slot at its lower end, and with the lips *d d* fitting loosely over the central bar, *a*, and the lips being sufficiently long to extend slightly below the lower edges of the bar. Now, to attach the
55 shank to the bar *a* it is only necessary to place the shank over the bar and upset the points or lips *d d* until they partially inclose the bar on each side, as shown in Fig. 2.

It is evident that while the hold which the
60 lips have upon the lower sides of the rectangular bar *a* may be comparatively slight, yet, as the only purpose sought is to prevent the bar *a* from slipping or falling away from the shank, the strength of the hold will be found to be
65 amply sufficient. By these simple means I am enabled to cast the shank, the pivots, and the wheels separately, finishing them up separately, and then quickly attach the parts together,
70 ready for use, thus greatly cheapening the cost of the caster without detracting in the least from its efficiency.

The shank C is constructed with the collar F and step *f* to receive the stem D. The stem D is provided with the flange G, which rests
75 upon the collar F, while the end of the stem is resting in the step *f*. Around the stem D is formed a groove, *g*. After the stem is in position, as shown in Figs. 1 and 2, the malleable
80 metal lip *i* on the collar F is forced into the groove *g*, by which means the stem is securely held in position, as shown in Fig. 2. The rollers may be secured in position on the pivots
85 by screws or any other well-known means. The flanges *b b*, cast upon the axle, are wider apart at the bottom than at the top, for the purpose of securing to the shank C a lateral
oscillation directly on the axle of the caster and between the wheels.

Having described my invention, what I
90 claim as new, and desire to secure by Letters Patent, is—

1. The shank C, provided with the collar having the malleable metal lip *i*, and the step *f*, in combination with the stem D, provided with
95 the groove *g*, substantially as and for the purpose set forth.

2. In a furniture-caster, the rollers A A and the pivots B B, rigidly connected by the rectangular bar *a*, and provided with the flanges
100

b b, in combination with the shank C, slotted at its lower end, and provided with lips *d d*, all constructed to operate substantially as and for the purpose herein described.

5 3. In a furniture-caster, the shank C, having its lower end slotted and provided with the lips *d d*, in combination with the pivots or axle

provided with the flanges *b b*, whereby the caster is secured oscillation directly on its shaft, as herein described.

OLE PEDERSON.

Witnesses:

J. B. THOMPSON,

PERRY P. SMYTHE.