



(No Model.)

E. S. AMROCK.  
COMBINED SETTEE AND LOUNGE.

No. 271,762.

Patented Feb. 6, 1883.



Witnesses A-  
A'  
E. S. Amrock  
T. P. Ryder

A-  
A' Inventor.  
E. S. Amrock  
by J. H. Adams  
Att'y



# UNITED STATES PATENT OFFICE.

EDWARD S. AMROCK, OF WALTHAM, MASSACHUSETTS.

## COMBINED SETTEE AND LOUNGE.

SPECIFICATION forming part of Letters Patent No. 271,762, dated February 6, 1883.

Application filed October 4, 1882. (No model.)

*To all whom it may concern:*

Be it known that I, EDWARD S. AMROCK, of Waltham, in the county of Middlesex and State of Massachusetts, have invented a new and useful Improvement in a Combined Settee and Lounge, of which the following is a specification.

The object of my invention is to produce a convenient, portable, and convertible settee and lounge, adapted for lawn purposes or any other outdoor use.

The invention consists of a frame composed of four inclined bars, having a top bar passing through holes in the upper ends of the inclined bars, and provided with a canvas or other suitable flexible material so connected with the inclined bars as to render it adjustable either in front or rear, and so as to form a support for the back when used as a settee.

The invention also consists of an adjustable head-rest secured to a cord or rope which acts as a support to the longitudinal side rails.

Referring to the drawings, Figure 1 is an end view of my convertible settee and lounge. Fig. 2 is a sectional view, showing the attachment of an adjustable awning. Fig. 3 is a front elevation. Figs. 4, 5, and 6 are detail views.

A A A' A' represent bars set at an inclination, as shown in Figs. 1 and 2.

B is a longitudinal bar secured to the upper ends of the inclined bars A A', through which the bar B passes, and is secured in place by a pin, or by means of a latch and groove in place of the pin, as shown in Fig. 5.

C C' are two longitudinal bars, which support the canvas or seat G, and are connected at the ends to the inclined bars A A' in such a way as to admit of their sliding freely on the bars A A'. The bars C C' are supported by means of cords D D', which pass through holes in the bar B, and they may also be further supported by means of a hinged bar or pawl, *f*, fitting in notches *g* in the bars A, as shown in Fig. 6. A spring-latch may be used to act automatically for the same purpose. Thus the seat and the back may be adjusted higher or lower, as desired.

E is a head-rest composed simply of a narrow strip of canvas or other suitable material, at each end of which is a wide hem, in which

is inserted a short bar, a hole being made through the canvas and the bars at the center of their length for the cords D D' to pass through, by means of which the head-rest is supported and rendered adjustable to any inclination or height, or lowered at either end, according to the angle at which the bars A A' are set, and also according to the position of the bars C C' on said bars A A'. The head-rest E is thus always kept in proper position relatively to the canvas G.

At each end of the top of the inclined bars A A' is a bar, H, pivoted or hung at its center to the projecting ends of the longitudinal bar B, so as to swing freely on the same. To these bars H is attached an awning, K. To each end of the bars H is attached a cord, *h*, extending downward and secured to bars A A', by means of which cords *h* the awning K can be fixed at any inclination for protection against the rays of the sun, or the wind, as desired. The awning-bars H may be secured in place by means of a circular bar or plate, H', Fig. 4, provided with holes or notches, or with a friction-clutch.

By means of the above-described construction the combined lounge and settee can be readily taken apart and the parts folded in a small compass for packing or transportation, and when required for use may be readily put together and set up.

Under the canvas G, I form a pocket, I, for containing clothes or other articles. This pocket can be of any desired size, and is formed by stitching a piece of canvas onto the canvas G, along two sides and one end thereof, and leaving one end or side open, which forms the mouth, and which can be secured by buttons or otherwise.

What I claim as my invention, and desire to secure by Letters Patent, is—

1. In a combined settee and lounge, the combination of the inclined bars A A', the bar B, the adjustable bars C C', the canvas G, or its equivalent, and the cords D D', substantially as and for the purposes set forth.

2. The combination of the adjustable pivoted bar H, the cross-bar B, the awning K, and cords *h h*, substantially as and for the purposes set forth.

3. In a combined settee and lounge, the

combination of the inclined bars A A', the swinging bar H, and the circular bar or plate H', provided with holes for the insertion of a locking-pin, substantially as set forth.

5 4. In a combined settee and lounge, the pocket I, in combination with the seat G, substantially as and for the purpose specified.

10 5. The adjustable head-rest E, consisting of a single strip of canvas, in combination with the cords D, canvas G, bar B, and support-

ing-bars A A', substantially as and for the purpose set forth.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

EDWARD S. AMROCK.

Witnesses:

JOS. H. ADAMS,  
E. PLANTA.