

(No Model.)

F. HANSON.

NAIL FOR CARRIAGE CURTAIN FASTENINGS.

No. 273,729.

Patented Mar. 13, 1883.




FIG. 1.




FIG. 2.




FIG. 3.





FIG. 4.

FIG. 5.



WITNESSES.

*Wm. J. Goodwin*  
*John P. Corrigan*

INVENTOR.

*Freeman Hanson*  
*Per attys.*

*Clifford and Clifford*

# UNITED STATES PATENT OFFICE.

FREEMAN HANSON, OF HOLLIS, ASSIGNOR TO GEORGE L. WARREN AND CHARLES F. WARREN, BOTH OF PORTLAND, MAINE.

## NAIL FOR CARRIAGE-CURTAIN FASTENINGS.

SPECIFICATION forming part of Letters Patent No. 273,729, dated March 13, 1883.

Application filed May 29, 1882. (No model.)

*To all whom it may concern:*

Be it known that I, FREEMAN HANSON, of Hollis, in the county of York and State of Maine, have invented certain new and useful  
5 Improvements in Nails; and I do hereby declare that the following is a full, clear, and exact description of the invention, which will enable other skilled in the art to which it ap-  
10 pertains to make and use the same, reference being had to the accompanying drawings, and to letters of reference marked thereon, which form a part of this specification.

Figure 1 is a side elevation. Fig. 2 is a side sectional elevation. Fig. 3 is a view of the  
15 body-top with the head removed. Fig. 4 is a side elevation of the top when removed from the body. Fig. 5 is a view of the body with the head removed.

My invention relates to nails to be used on  
20 carriages or house-walls for holding carriage-curtains, picture-cord, &c.

It consists of the combination of a removable head, *a*, with shank *b*, and spring *c*, with the body *d*, having the socket *e*, lips *f*, and  
25 shoulders *g*, and the screw or nail formed shank *h*.

My invention is designed to be applied to nails where it is desirable to have a removable head, easily removable and capable of be-  
30 ing securely attached to the body.

The button-holes of carriage-curtains are continually being torn out by the pulling of the curtain off over the head of the button. Annoyance and expense are occasioned by this.  
35 When torn to a certain extent the expense of new curtains has to be incurred. This is produced by the fact that the head has to be large enough to hold the curtain securely, and thus the button-hole goes over the head with difficulty and fits tightly, and so the head is apt  
40 to tear out the hole.

With my invention the button-hole is passed over the body *d* of the nail, and then the head is pressed into place, and when the curtain is  
45 to be taken off the head *a* is quickly removed and the curtain taken off the carriage without liability of tearing.

In cases where it is desirable to have a nail with an ornamental head—as a picture-nail—then the nail must be driven and the head put  
50 on afterward. A common contrivance for this purpose now in use is a nail with a screw-socket. I do not of course claim such an arrangement.

The socket *e* is somewhat larger than the  
55 shank *b*, so that there is room for the two-armed flaring spring *c*. The ends of this spring fit up against the lips *f*, and so hold the head in place. The shoulders *g* meet the edges of the  
60 spring *c* and prevent the head *a* from being turned any farther. Thus the head has to be turned in one particular direction in order to be turned out. The body *d* is furnished with the nail or screw *h*, and can be attached by  
65 either means, as desired. When driven into place, then the head *a* is taken off while driving.

If a hole is made in the place into which the device is to be placed and the screw is used, as seen in the drawings, then the head can be  
70 kept on and the device sent to its place by turning with the thumb and finger.

I do not claim a nail with a removable head, which head is capable of being held in place  
75 when desired.

My invention covers the combination of de-  
80 vices herein described, operating as set forth.

What I claim as my invention, and desire to secure by Letters Patent of the United States, is—  
85

In a nail having a removable head, the combination of the head *a*, shank *b*, the two-armed flaring spring *c*, the lips *f* of the socket, the shoulders *g*, to check the rotation of the head  
85 when turned, the body *d*, having the socket *e*, and a nail or screw, *h*, as herein set forth.

In testimony that I claim the foregoing as my own I affix my signature in presence of two witnesses.

FREEMAN HANSON.

Witnesses:

WILLIAM HENRY CLIFFORD,  
GEO. L. WARREN.