




(No Model.)

J. BRANDT.

MACHINE FOR CUTTING OUT CIGAR WRAPPERS.

No. 277,452.

Patented May 15, 1883.



Witnesses:
Wm. Voigt
Geo. Vincent

Inventor:
Jacob Brandt
By his Atty., *Edw. J. Brown*

UNITED STATES PATENT OFFICE.

JACOB BRANDT, OF SAN FRANCISCO, CALIFORNIA.

MACHINE FOR CUTTING OUT CIGAR-WRAPPERS.

SPECIFICATION forming part of Letters Patent No. 277,452, dated May 15, 1883.

Application filed August 31, 1882. (No model.)

To all whom it may concern:

Be it known that I, JACOB BRANDT, of the city and county of San Francisco, in the State of California, have made and invented certain
5 new and useful Improvements in Machines for Cutting Out Cigar-Wrappers; and I do hereby declare that the following is a full, clear, and exact description of the same, reference being had to the accompanying drawings.

10 My invention relates to an improved machine for cutting out a number of wrapper-blanks at a single operation from a pile of material.

The object sought to be attained by my improvement is to provide a machine capable of
15 cutting out wrapper-blanks of any given form in greater or less quantity, with a clean-cut or smooth edge, and having the capacity to work for a long time without clogging. These objects I attain in the following manner by the mechanism illustrated in the accompanying
20 drawings, in which—

Figure 1 is a side elevation of my improved machine, the bed-plate and cutting-slab being
25 in section. Fig. 2 is a transverse section taken through the cutter, the plunger, and the slab. Fig. 3 is a perspective view of the cutter, and Fig. 4 a view of the plunger that works within

30 An upright post or standard, A, secured to a suitable bed or table, A', has bearings *b b* for a vertically-moving bar or rod, B. This bar carries the cutter-block C on its lower end, and at the upper end is connected to a hand-lever,
35 D, by which a downward movement of the bar and pressure upon the cutter is produced. The fulcrum *d* of this lever is placed in a swinging yoke, F, formed of two bars, the lower ends of which are pivoted at *f* to the
40 back of the standard at the lower end. This permits the fulcrum-point *d* to move outwardly as the lever is brought down into the horizontal position. The upward movement of the bar to retract the cutter is produced by a spiral
45 spring, *g*. The cutter-head fixed to the end of this bar B is of peculiar construction. It consists of a cutting-edge, *h*, formed of a continuous blade of the outline of the wrapper to be produced, and secured to a block so as to be
50 removable when required to be changed. In the space within this cutting-edge is a plunger

or presser plate, I, having a shape to conform to the space inclosed by the cutting-edge and held in position by rods or pins *j*, that project upward and through the top of the block C. 55 The block C is provided with openings *c* to allow the air to escape freely as the plunger is forced upward, so that the spiral springs shall be the only resistance which the plunger shall meet in its rise. These are readily adjusted in
60 their force, as the plunger is set higher or lower by the nuts on the rods *j*. The object of this plate I is to force out the blanks from within the cutter as soon as the cutting operation is completed and the block C is raised 65 from the cutting-slab. The plunger also serves to cleanse and moisten the cutter, for which purpose its edges are covered with some suitable substance or material capable of receiving and holding water, such as a sponge or a
70 piece of felt. For this purpose it is made of two plates, *i i*, between which the moistening material is firmly clamped, and the top plate is perforated with a number of holes, and the top of the cutter-head provided with an open- 75 ing, through which water is supplied to the plate. A similar moistening and cleansing device can be applied on the outside of the cutting-blade, if required, so that the two surfaces of the die can be kept from gumming or
80 becoming clogged.

It is also of advantage to keep the faces of the cutter moistened during the operation of the machine, in order to produce a clean, smooth edge on the wrapper-blank. The same 85 can be obtained, however, by using the inside moistener alone, as it is not essential to prevent the material outside of the line of cut from chipping or breaking.

The outside moistener, K, may be formed of 90 a frame fastened at the side to the table and having its interior edges or surfaces covered with the moistening substance.

The cutting board or slab L is movable in and out and has a guide-plate, *m*, which serves 95 as a guide to lay the edge of the leaves against when placing them in a pile or layer upon the board.

This machine can be made to cut a large number or a pile of leaves at a single operation and to turn out blanks with smooth-cut 100 edges in a rapid and effective manner.

Having thus fully described my invention, what I claim, and desire to secure by Letters Patent, is—

5 1. In a cigar-blank cutter, the combination of the rod B and cutter h and block C, provided with the air-holes c, of the plunger I, having the adjustable supports and spring-bearing, and of the lever D and swinging yoke F, substantially as herein set forth.

10 2. The combination, with the reciprocating cutter C, of the plunger I, having the moistening substance at and around the edges, substantially as and for the purpose set forth.

3. The combination, with the hollow reciprocating cutter, of the plunger having the moistening device, and the outer frame, K, carrying moistening substance and working in contact with the edge of the cutter, substantially as described.

Witness my hand and seal.

JACOB BRANDT. [L. S.]

Witnesses:

EDWARD E. OSBORN,
D. SELLECK.